


DIN 6388 COLLETS
PINZAS DIN 6388
SPANNZANGEN NACH DIN 6388



002 04

(With clamping field) For plain straight shank tools.
 (Gran elasticidad) Sujeción de mangos cilíndricos lisos.
 Für Werkzeuge mit zylindrischem Schaft, doppelseitig geschlitzt.

FORM B



COD.	D	L	D1	Clamping field Campo Spannfeld	Availability Disponibilidad Verfügbarkeit
002 04 03	25,5	40	3-6,5-7-7,5-8-8,5-10 11,5-12-12,5-14,5-15-15,5	-0,5	☐
002 04 04	29,8	45	7,5-8-9-9,5-11-11,5-13 13,5-14,5-15-15,5-17-17,5-19	-0,5	☐
002 04 05	35,05	52	6,5-7-8-8,5-10-11-12-14 15,5-16,5-18-18,5-19,5-20-25	-0,5	☐
002 04 06	43,7	60	6-7-8-9-9,5-10-10,5-11-11,5-12-12,5-13-14 14,5-15-15,5-16-16,5-.....32	-0,5	☐
002 04 07	52,2	68	10,5-11,5-.....31,5	-0,5	☐

- To order: COD. + D1.
 Example: 002 04 04/10
 - Material: Tempered
 spring steel
 - Hardness: 46 ÷ 48 HRC

- Forma de pedido: COD. + D1.
 Ejemplo: 002 04 04/10
 - Material: Acero de muelles
 templado
 - Dureza: HRC 46 - 48 HRC.

- Für Bestellung: COD. + D.
 Beispiel: 002 04 04/10
 - Werkstoff: Federstahl
 - Oberflächenhärte: 46-48 HRC.

COLLETS FOR TAPPING CHUCKS AND FOR DIN 6388 COLLET CHUCKS
PINZAS PARA PORTAMACHOS Y PORTAPINZAS DIN 6388
SPANNZANGEN FÜR GEWINDEBOHRER NACH DIN 6388




002 19

For cylindrical straight shanks
 with square DIN 10.

Sujeción de mangos
 cilíndricos DIN 10.

Für Werkzeuge mit zylindrischem
 Schaft nach DIN 10.



COD.	CAP.	D	L	d	∅	L1	L2	Availability Disponibilidad Verfügbarkeit
				2,5	2,1	19	15	☐
				2,8	2,1	19	15	☐
				3,15	2,5	22	18	☐
				3,5	2,7	21	16	☐
				3,55	2,8	22	18	☐
				4	3	21	16	☐
				4,5	3,4	21	16	☐
				5	4	25	19	☐
				5,5	4,3	24	18	☐
002 19 03	M3-M16	25.4	52	5,6	4,5	25	19	☐
				6,3	5	28	22	☐
				7	5,5	26	19,5	☐
				7,1	5,6	28	22	☐
				9	7	30	22	☐
				10	8	32	23	☐
				11,2	9	36	26	☐
				6	4,9	26	19,5	☐
				6,3	5	28	22	☐
				7	5,5	26	19,5	☐
				8	6,2	27	19,5	☐
				9	7	30	22	☐
002 19 04	M8-M28	29.8	63	10	8	32	23	☐
				11	9	34	24	☐
				12	9	36	25	☐
				14	11	38	26	☐
				16	12	44	30	☐

- To order: COD. + D1.
 Example: 002 19 04 10 08
 - Material: Tempered
 spring steel
 - Hardness: 57 ÷ 60 HRC.

- Forma de pedido: COD. + D1.
 Ejemplo: 002 19 04 10 08
 - Material: Acero de muelles
 templado
 - Dureza: HRC 57- 60.

- Für Bestellung: COD. + D. Beispiel:
 002 19 04 10 08
 - Werkstoff: Federstahl
 - Oberflächenhärte: 57-60 HRC.