

ENC

linear guides

HS H SERIES

SIN ALAS



Guía

	Tornillo de montaje	Din carga	Stat. carga	Máx. impulso estático (kN-m)			Peso (Kg/m)	Dimensiones montaje (mm)			Dimensiones guía (mm)						
Código	(mm)	C(kN)	C0(kN)	MR	MP	MT	Guide	H	H1	N	WR	HR	D	h	d	P	E
HS R 15 R 4000 C	M4x16	11.38	25.31	0.17	0.15	0.15	1.45	28	4.3	9.5	15	15	7.5	5.3	4.5	60	20
HS R 20 R 4000 C	M5x16	17.75	37.84	0.38	0.27	0.27	2.21	30	4.6	12	20	17.5	9.5	8.5	6	60	20
HS R 25 R 4000 C	M6x20	26.48	56.19	0.64	0.51	0.51	3.21	40	5.5	12.5	23	22	11	9	7	60	20
HS R 30 R 4000 C	M8x25	28.74	83.06	1.06	0,85	0,85	4,47	45	6	16	28	26	14	12	9	80	20
HS R 35 R 4000 C	M8x25	49.52	102.87	1.73	1.20	1.20	6.30	55	7.5	18	34	29	14	12	9	80	20
HS R 45 R 4000 C	M12x35	77.57	155.93	3.01	2.35	2.35	10.41	70	9.5	20.5	45	38	20	17	14	105	22.5

Patín

	Tornillo de montaje	Din carga	Stat. carga	Máx. impulso estático (kN-m)			Peso (Kg/m)	Dimensiones montaje (mm)			Dimensiones patín (mm)											
Código	(mm)	C(kN)	C0(kN)	MR	MP	MT	Block	H	H1	N	W	B	B1	C	L1	L	K1	G	MxI	T	H2	H3
HS H 15 CA Z0 C	M4x16	11.38	25.31	0.17	0.15	0.15	0.18	28	4.3	9.5	34	26	4	26	39.4	61.4	10	5.3	M4x5	6	7.95	7.7
HS H 20 CA Z0 C	M5x16	17.75	37.84	0.38	0.27	0.27	0.30	30	4.6	12	44	32	4	36	50.5	77.5	12.25	12	M5x6	8	6	7
HS H 25 CA Z0 C	M6x20	26.48	56.19	0.64	0.51	0.51	0.51	40	5.5	12.5	48	35	6.5	35	58	84	16.8	12	M6x8	8	10	13
HS H 30 CA Z0 C	M8x25	38.74	83.06	1.06	0.85	0.35	0.38	45	6	16	60	40	10	40	70	97.4	20.25	12	M8x10	8.5	9.5	13.8
HS H 35 CA Z0 C	M8x25	49.52	102.87	1.73	1.20	1.20	1.45	55	7.5	18	70	50	10	50	80	112.4	20.6	12	M8x12	10.2	16	19.6
HS H 45 CA Z0 C	M12x35	77.57	155.93	3.01	2.35	2.35	2.73	70	9.5	20.5	86	60	13	60	97	139.4	23	12.9	M10x17	16	18.5	30.5

MR

MP

MY

