

Maximum Substrate Size	5 in. x 5.75 in. (125 x 144 mm)
Speed Mode (Inches Per Minute)	3 to 50 in/min. (7.5 to 125 cm/min.)
Time Mode (Dwell & Travel Time)	1 sec. to 99 min. 59 sec. (per zone)
Temperature (Standard)	Up to 420°C
Temperature Accuracy	± 2°C
Warm-up Time to 230°C	10 minutes
Coolant Flow	0.5 to 2 GPM (2 to 8 liters/min.)
Alarms	Over/Under Temperature, Gas, Coolant, Motor Torque
Parts Flow (Specify When Ordering)	L to R or R to L
Gas Consumption	120-150 cubic feet per hour
O ₂ Level	10 PPM, 0.25 inch opening
Voltage (Specify when Ordering)	200 to 240 VAC, 50/60 Hz, 1 or 3 Phase
Start-up Power (kW)	11kW @ 240 VAC
Power Consumption	50% or less
Basic Unit Weight	200 lbs. (91 Kg)
Basic Unit Dimensions	L 53 x W 25 x H 26 inches (134.6 x 63.5 x 66 cm)

For More Information Contact Sales at Sikama International.

Sikama International Inc.
118 East Gutierrez Street
Santa Barbara, Ca. 93101-2314
Phone: (805) 962.1000
Fax: (805) 962.6100
Email: sales@sikama.com
Web: www.sikama.com