

Thermo-chiller/ Rack Mount Type

RoHS

HRR Series



How to Order

Air-cooled Refrigeration

HRR 012 - A - 20 -

● Cooling capacity ●

012	1000/1200 W (50/60 Hz)
018	1600/1800 W (50/60 Hz)
024	2000/2400 W (50/60 Hz)
030	2500/3000 W (50/60 Hz)

● Cooling method ●

A	Air-cooled refrigeration
---	--------------------------

● Pipe thread type ●

Nil	Rc
F	G (With Rc-G conversion fitting set)
N	NPT (With Rc-NPT conversion fitting set)


● Option ●

Nil	None
DM	With electric conductivity control function, Applicable to DI water piping
M	Applicable to DI water piping
T	High-pressure pump mounted
U	Conforming to UL Standards
Y	With feet/Without rack mounting brackets

· When multiple options are combined, indicate symbols in alphabetical order.

● Power supply ●

Single-phase 200 to 230 VAC (50/60 Hz)



Water-cooled Refrigeration

HRR 012 - W - 20 - U -

● Cooling capacity ●

012	1000/1200 W (50/60 Hz)
018	1600/1800 W (50/60 Hz)
024	2000/2400 W (50/60 Hz)
030	2500/3000 W (50/60 Hz)

● Cooling method ●

W	Water-cooled refrigeration
---	----------------------------

● Pipe thread type ●

Nil	Rc
F	G (With Rc-G conversion fitting set)
N	NPT (With Rc-NPT conversion fitting set)

● Option 2 ●

Nil	None
Y	With feet/Without rack mounting brackets

● Option 1 ●

Nil	None
DM	With electric conductivity control function, Applicable to DI water piping
M	Applicable to DI water piping
T	High-pressure pump mounted

· When multiple options are combined, indicate symbols in alphabetical order.

● Power supply ●

Single-phase 200 to 230 VAC (50/60 Hz)

