

## Specification Date Sheet | Model: EBD1200-EU(W)



### ENVIROBULKA Deluxe 5300 LITRES

- ❖ Robust steel in steel construction ensures security, whilst 110% weatherproof bund complies with environmental requirements for fuel storage.
- ❖ Pump, nozzle, hoses and generator feed & return connections are all housed within secure, lockable bund compartment. Feed and return hoses can be fed through openings enabling generator to be run whilst connections are kept secure in compartment – helps to prevent theft and vandalism
- ❖ Manhole providing access to inner tank for maintenance and inspection
- ❖ Fitted with lifting eyes and forklift access for ease of handling while empty and relocation of tank.
- ❖ All outlets are top mounted above fuel level helping prevent weepage of fuel. Optional anti-siphon valve available for extra environmental protection.
- ❖ 3-Point locking mechanism for additional security.
- ❖ Cabinet Drip Tray with galvanised H/D tread mesh.
- ❖ Bund sensor to detect fluid in bund.

### SPECIFICATION

Standard Tank Fittings : 2" Fill Point : 2" Vent : Sight Glass : Contents Gauge : 1" Pump Feed : Extra 2" Fill Point : 2 x 1/2" Generator Feed & Return Ports : 2 Spare 1 1/4" Ports for additional equipment : Bund Drain Pipe : Bund Alarm			
Capacity (Brim Full) Litres:	5300	Bund Material (Thickness):	S235JR (3mm)
Capacity (Brim Full) Gallons:	1165	Inner Tank Material (Thickness):	S235JR (3mm)
Dimensions Length (mm):	3000	Weight Empty (Approx kg):	1430
Dimensions Width (mm):	1150	Weight Laden (Approx kg):	5885*
Dimensions Height (mm):	2475	Design Standards:	BS799 & PPG2
Cabinet Dimensions (mm) Opening Size: Width 850 x Height 1700: Depth 580			
Notes			
*Specific gravity of diesel taken as 0.9 for this calculation.			

Revision Date: 02/12/2014