



FOR NEW EQUIPMENT SALES, CALL
800.958.2555
TO SPEAK WITH AN ALTEC REPRESENTATIVE
or visit us online at altec.com

Altec
OVERCENTER
AERIAL DEVICE

AN SERIES


FEATURES

- Platform Leveling System - Chain and Rod in Lower and Upper Booms
- Lower Boom Non-Overstow Protection System
- Access to Ground in Non-Overcenter Position (Extended Reach Models Only)
- Hydraulic Platform Tilt
- Material Handling System with Hydraulic Extended Jib
- Altec ISO-Grip® Control System
- Outrigger Boom Interlock System and Motion Alarms
- Electric/Hydraulic Outrigger Controls
- Two Sets of Hydraulic Tool Circuits at Each Platform
- Diagnostic Pressure Test Quick Disconnect Couplings
- 90° Hydraulic Platform Rotator(s) with Side Mount Jib
- Emergency Stop Valves at all Upper and Lower Control Stations
- Pilot Pressure System
- Insulating, ANSI Category C

OPTIONS

- Automatic Upper Boom Stow System
- Engine Start/Stop
- 24 in Platform Elevator
- Remote Secondary Stowage System
- Jib Adapter
- Phase Lifting Jib Attachment
- Platform Options
 - » Single, One-Man Platform
 - » Single, Two-Man Platform
 - » Dual, One-Man Platform
- Insulating, ANSI Category B
- Lanyard Interlock/Alarm Available on Select Platform Configurations
- Altec Load Monitoring System (Available on Select Models)

REACH DIAGRAM



Recommended safety equipment, available through Altec Supply, include a platform liner, fall protection system, wheel chocks and outrigger pads.

OPTIONAL JIB PLACEMENT BETWEEN ONE-MAN PLATFORM AND BOOM TIP



AN46(E)OC: DESIGNED FOR CONFINED WORKING AREAS USING AN 84 IN OR 102 IN CA



CONFIGURATIONS

AN46OC AN50OC AN55OC AN46EOC AN50EOC AN55EOC

Ground to Bottom of Platform*	48.3 ft (14.8 m)	51.5 ft (15.7 m)	56.5 ft (17.2 m)	48.3 ft (14.83 m)	51.5 ft (15.7 m)	56.5 ft (17.2 m)
Working Height*	53.3 ft (16.4 m)	56.5 ft (17.2 m)	61.5 ft (18.8 m)	53.3 ft (16.4 m)	56.5 ft (17.2 m)	61.5 ft (18.8 m)
Maximum Side Reach (Non-Overcenter)	32.1 ft (9.9 m)	34.4 ft (10.6 m)	37.8 ft (11.6 m)	36.7 ft (11.3 m)	39.3 ft (12.0 m)	43.3 ft (13.2 m)
Maximum Side Reach (Overcenter)	42.1 ft (12.9 m)	45.3 ft (13.8 m)	50.3 ft (15.3 m)	42.1 ft (12.9 m)	45.3 ft (13.8 m)	50.3 ft (15.3 m)
Platform Capacity	Up to 700 lb (318 kg)					
Stowed Travel Height*	11.7 ft (3.6 m)					
Maximum Jib Capacity	2,000 lb (907 kg)					
Lower Boom Articulation	0 to 105°	0 to 105°	0 to 105°	0 to 120°	0 to 120°	0 to 120°
Upper Boom Articulation	0 to 192°	0 to 196°				
Rotation	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous

*Based on a 40 in (1016 mm) chassis frame height.

For more complete information on Altec products and services, visit us on the web at www.altec.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission.

© 2020 Altec Inc. All Rights Reserved. A10SANOCSERIES-120



NEW EQUIPMENT SALES

800.958.2555

SALES@ALTEC.COM

ALTEC.COM