

PULPER V-BELT DRIVE Certification Sheet

IDENTIFICATION	CUSTOMER <u>Schweitzer-Mauduit</u> ADDRESS (ORDER) <u>Lee, MA</u> ADDRESS (INSTALL) <u>Same</u> CUSTOMER P.O. NO. <u>65970</u> DATED <u>2-3-2004</u> CUSTOMER EQUIPMENT NO. <u>N/A</u> CONTROLS BY <u>Customer</u> CERTIFIED BY <u>Leo V. Fuerst</u>		CUSTOMER DESIGNATION <u>N/A</u> TYPE <u>BR1067-45/4 HOAV</u> SERIAL NO.* <u>45-4 HOAV-361</u> VOITH PAPER JOB NO. <u>101348</u> VOITH PAPER ORDER DATE <u>2-18-2004</u> CONTROLS SERIAL NO.* <u>N/A</u> TITLE <u>Senior Product Designer</u>	
APPLICATION	INSTALLATION DWG. <u>887804804</u> STOCK <u>Virgin</u> STOCK CONSISTENCY <u>6.0%</u> BD pH ____ TEMP ____ °F OPERATING MODE <u>BATCH</u> TANK BY <u>Voith</u> DIM.: <u>184"</u> I.D. HEIGHT <u>155.50"</u> CAP. AT OPER. LEVEL <u>1067</u> CU. FT. IMPELLER RPM <u>268</u> EXTRACTION HOLE SIZE <u>0.38</u> BLADE TYPE <u>H206</u> EXTRACTION NOZZLE: <u>18.00"</u>			
MATERIAL	PULPING UNIT <u>316L / MS / CI</u> EXTRACTION PLATES <u>316L</u> TANK <u>316L / 304L</u> EXTRACTION CHAMBER <u>316L / MS</u>			
DRIVE	DRIVE BY <u>Voith</u> V-BELT/POWERBAND NO. <u>2</u> SIZE <u>(3) 8V4000</u> C.D. <u>128.7"</u> MOTOR SHEAVE <u>6</u> GR <u>8</u> V <u>16.0"</u> O.D. BORE <u>3.88</u> <u>1.00 x 0.88</u> SHALLOW KEY DRIVEN SHEAVE <u>6</u> GR <u>8</u> V <u>71.0"</u> O.D. BORE <u>6.50"</u> <u>1.50 x 1.00</u> SHALLOW KEY BELT PULL ON MOTOR <u>4914</u> LBS.			
MOTOR	MOTOR BY <u>Customer</u> FRAME SIZE <u>5011L</u> HP <u>300</u> RPM <u>1190</u> <u>4160</u> V <u>3</u> PH <u>60</u> HZ			
OPTIONS	<u>FURNISHED ONLY IF MARKED</u> ☐ CONTROL PANEL ☒ BELT GUARDS ☒ STEAM VALVES ☐ ____ " JUNK TRAP ☐ TANK MANWAY ☐ ____ " DUMP VALVE ☐ ADJ. MOTOR BASE			
REMARKS	*ALWAYS SPECIFY UNIT SERIAL NO. WHEN ORDERING SPARE PARTS.			