

Sliding table saw

minimax si 400es 26 ALU 2

Heavy-duty version and anodised aluminum format sliding carriage specially designed for cutting aluminum and plastic



Article Number ▼

3624790

Additional Costs ▼

Total 159.00 €

TPZ750 100.00 €

TVP3 59.00 €

Availability ▼

No stock available

Delivery time on request

Next availability

Expected on calendar week 06/2021



Brand ▼

Metallkraft

Catalog Path ▼

Metalworking machines » Sliding table saws

Order ▼

Minimum 1 pc(s).

Shipment Informations ▼

Packaging Metrics		Weights		Delivery	
Length	n/a	Gross	700 kg	Delivery	Carrier
Width	n/a	Net	700 kg	Content	1 pc(s).
Height	n/a				

Description ▼

- Smooth-running anodized aluminum sliding carriage
- Large table boom (can be moved longitudinally) with roll of material on telescopic arm
- Extendable telescopic crosscut fence with two hinged stops
- Precise rip fence, hinged for large panels, with quick clamping and integrated fine adjustment
- Standard with table extension, with table extension and eccentric tensioner
- Saw unit made of a sturdy cast iron ring shape with double swivel segment guide (double cradle) and zero point swivel for a smooth and perfect cut
- Large work table made of stress-free gray cast iron
- On / off switch on sliding carriage
- High dead weight ensures precision and quiet running
- Two cutting speeds switchable via inverter
- Wegschwenkeinrichtung for stop under the table
- Cutting width 1270 mm

Delivery Contents ▼

- Anodised aluminum sliding carriage
- Roll of material on the boom
- Saw rip fence with round bar guide
- table extension
- table extension
- folding stops
- edging shoe
- Eccentric
- Handle for sliding carriage
- Saw blade swing protection
- Mikrosprüheinrichtung
- 2 saw blade speeds, electronically adjustable via inverter

Technical Data ▼

Dimensions and weights			
Net weight approx.		700 kg	
Extraction port			
Extraction port diameter bottom		120 mm	Saw blade protection extraction port diameter 80 mm
Footprint			
Transport width		990 mm	Length 1900 mm
Width/depth		885 mm	Space requirement length 5890 mm
Space requiremen width/depth		4860 mm	Explanation about space requirement The dimensions take into account maximum travel distances or usable lengths
Work area length		1600 mm	Work area width/depth 2300 mm
Explanation about work area		Please add the given dimensions with the required space to obtain the free space recommended for the machine.	
Electric Data			
Supply voltage		400 V	Phase(s) 3 Ph
Current type		AC	Mains frequency 50 Hz
Drive motor output		7.0 kW	
Sliding carriage and table			
Trimming frame length		2600 mm	Sliding carriage length 2600 mm
Sliding carriage width		360 mm	Sliding carriage height 142 mm
Table length		940 mm	Table width 560 mm
Work height		900 mm	
Circular saw unit			
Max. cutting width with rip fence		1270 mm	Max. cross cut width left from saw blade 3260 mm
Trimming length		2600 mm	Saw blade angle 90 - 45 °
Max. cutting height 90°		138 mm	Max. cutting height 45° 98 mm
(Main) saw blade diameter		400 mm	(Main) saw blade speed 4200 min ⁻¹

Set Articles ▼



Sliding table saw minimax si 400es 26 ALU 2

Heavy-duty version and anodised aluminum format sliding carriage specially designed for cutting aluminum and plastic

Article Number ▼

5504790

Availability ▼


No stock available
Delivery time on request
Next availability
Expected on calendar week
06/2021

Order ▼

Minimum 1 pc(s).

**Price Informations** ▼

Options Equipment ▼



Degree grid division on the outrigger table

Article Number ▼


5510403

Availability ▼

In stock
Immediate delivery

Order ▼

Minimum 1 pc(s).

**Price Informations** ▼

Digital display of the working width at the rip fence PA-DIGI-SI

Article Number ▼

5514349

Availability ▼

No stock available
Delivery time on request
Next availability
Unknown

Order ▼

Minimum 1 pc(s).

**Price Informations** ▼

Trimming frame with CompeX device

Article Number ▼

5514380

Availability ▼

No stock available
Delivery time on request
Next availability
Unknown

Order ▼

Minimum 1 pc(s).

**Price Informations** ▼

Longitudinal stop with three LCD displays of the stop position

Article Number ▼

5514392

Availability ▼

No stock available
Delivery time on request
Next availability
Unknown

Order ▼

Minimum 1 pc(s).


**Price Informations** ▼

Accessories



Extraction system connection set 120/80 mm



Article Number 
5146080

Availability 
In stock
Immediate delivery


Order 
Minimum 1 pc(s).

Price Informations 



Miter fence 1060 mm, with telescopic guide



Article Number 
5514315

Availability 
In stock
Immediate delivery


Order 
Minimum 1 pc(s).

Price Informations 




Additional work table on the sledge




Article Number 
5510402

Availability 
In stock
Immediate delivery


Order 
Minimum 1 pc(s).


Price Informations 



Digital display of the working width at the rip fence PA-DIGI-UNI




Article Number 
5516000

Availability 
No stock available
Delivery time on request
Next availability
Expected on calendar week
53/2020

Order 
Minimum 1 pc(s).


Price Informations 




HM saw blade Ø 400 x 4,0 x 30 mm Z72 positive



Meets the highest quality level especially for industrial applications on stationary machines

Article Number 
3650400

Availability 
In stock
Immediate delivery

Order 
Minimum 1 pc(s).

Price Informations 



Flat trapezoidal tooth saw blade

KSB-ZF 305/96

It meets the highest quality level especially for industrial applications on stationary machines



Article Number ▼

5263161

Availability ▼

In stock

Immediate delivery

Order ▼

Minimum 1 pc(s).

Price Informations ▼

The prices quoted are subject to change. Price changes reserved. Our terms and conditions apply. Jurisdiction is Bamberg. The place of performance is Hallstadt as agreed.