

Model 7360BT wall-mounted eye/face wash features a round 11" stainless steel receptor, aluminum wall bracket, and twin Feather-Flo® ABS plastic eye/face wash heads. Model is supplied with a waste tailpiece and trap. Supply: 1/2" IPS. Waste: 1-1/2" IPS.

Model 7360BT is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.

Components:

Eye/Face Wash Head Assembly: Model SP69FC eye/face wash assembly has twin SP21FC Feather-Flo® ABS plastic eye/face wash heads in Safety Green with integral flip top dust covers that protect heads and automatically release with water pressure.

Eye/Face Wash Head: Model SP21FC Feather-Flo® ABS green plastic eye/face wash head with built-in 2.5 gpm flow control with integral flip top dust cover that automatically releases with flow of water. 1/4" IPS.

Receptor: Model SP90 11" round stainless steel with No. 2L bright finish on exterior.

Eyewash Valve: Model SP229 chrome-plated brass stay-open ball valve, equipped with a stainless steel ball and stem. Full flow occurs with push on stainless steel flag. 1/2" IPS inlet and outlet.

In-Line Strainer: Model SP509 chrome-plated brass in-line 50 x 50 mesh water strainer that prevents debris from reaching the eye or eye/face wash. Easily serviceable. 1/2" IPS inlet x 1/4" IPS outlet.

Trap: Model SP95 chrome-plated brass trap with tailpiece. 1-1/2" IPS.

Mounting: Model SP80 cast-aluminum wall bracket with chromate protective finish.

Universal Sign: Model SP175 vertical universal emergency eyewash sign. Size: 8" x 10-3/4".

Test This Week Tag: SP170 is a green waterproof test card with space for date and initials of inspector. Used to record weekly testing of emergency equipment.

7360BT



Options/Accessories: (Additional costs may apply)

Eye/Face Wash: Model 7360B wall-mounted Feather-Flo® eye/face wash less trap.

Tempered Water Blending Systems: Model TWBS.EW, tempered water blending system, prepackaged, fully engineered and tested system with redundant fail-safe features to produce up to 5 gpm tempered water for eyewashes.

Tempered Water Blending Valves: Model 9201 thermostatic mixing valve that mixes hot and cold water for the tempering of water for eyewash units. Maximum flow rate is 21 gpm.

Dust Cover: Model 9102 stainless steel cover protects eye, eye/face wash and spray ring as well as bowl. Pushing the flag valve raises the dust cover and activates unit.

Foot Treadle: Model SP220W wall-mounted foot control assembly, including chain, ring, screw, spring, wall mounting bracket and powder-coated aluminum treadle.

Alarm: Model 9001.5 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by flow switch when emergency shower or eyewash is in use.

DISCLAIMER: Continued product improvements make specifications subject to change without notice. Check www.hawsco.com for the latest product information and updates.