

# Thermo Scientific Compact Digital Mini Rotator

Realize maximum flexibility with the easy-to-use, digitally-controlled rotator that provides smooth, quiet horizontal mixing of different tube/vessel types.

## FEATURES

- PID control ensures consistent and smooth rocking motion
- Digital Speed Control: 50 to 300rpm
- Timer Range: Continuous or 1min to 99hrs 59min
- Wide variety of accessories to customize unit for exact laboratory needs
- Compact design ideal for placing in incubators (non-CO<sub>2</sub>), chambers, and refrigerators (up to 60°C)



## APPLICATIONS

| Bacteria and fungi culturing | Hybridization assays  
Gel staining/de-staining

10

### Ordering Information and Specifications

Cat. No.	88880025*	88880026*
Plug Configurations		
Max. Load	4kg / 8.8lbs	
Control	Feedback Control PID	
Display	Digital	
Speed Range	50-300rpm	
Accuracy at 100rpm	+/- 5rpm	
Orbit Size	13 mm / 0.51in diameter	
Maximum Load	4 kg/8.81lbs	
Dimensions	<b>Platform:</b> (W x D) 250 x 250mm / 9.8 x 9.8in <b>Overall:</b> (W x D x H) 276 x 334 x 130mm / 10.9 x 13 x 5.1in	
Weight	8kg / 17.6lbs	
Power	100 – 240V, 50/60Hz	
Certifications	CE	
Warranty	2 Years	

**\*NOTE: Unit must be ordered with a platform**

### Accessories for the Compact Digital Mini Rotator

	Max. Mountable Flask Clamps	Cat. No.
Universal Attachment	N/A	88880104
Universal Platform	N/A	88880106
Flask Clamp for Shakers metal 50ml**	16	88880107
Flask Clamp for Shakers metal 100ml**	9	88880108
Flask Clamp for Shakers metal 250ml**	9	88880109
Flask Clamp for Shakers metal 300ml**	9	88880110
Flask Clamp for Shakers metal 500ml**	5	88880111
Flask Clamp for Shakers metal 1L**	4	88880112
Flask Clamp for Shakers metal 2L**	1	88880113

\*\* Flask clamps sold individually

