

TABLE 2
GAS FLOW RATE

Nominal Pipe Size, in.	Operating Pressure of Coil, psig									
	6000	5000	4000	3500	3000	2000	1500	1000	750	500
	Gas throughput to provide 80 ft/sec coil velocity @ 120°F, MMSCFD									
1 XS	-	12	11	9	8	6	4	2	1.5	1
2 Std	-	-	-	-	-	25	18	11	8	5.7
2 XS	-	-	-	-	33	22	16	10	7	5
2 XXS	30	28	25	23	20	13	10	6.5	4	2
2-1/2 Std	-	-	-	-	-	36	26	17	12	2
2-1/2 XS	-	-	-	53	47	32	23	15	11	8
2-1/2 XXS	41	38	34	31	28	19	13	9	6	4
3 Std	-	-	-	-	-	53	40	25	18	11
3 XS	-	-	-	-	74	47	36	22	16	10
3 XXS	70	65	58	54	46	31	23	14	10	7
4 Std	-	-	-	-	-	95	70	43	30	20
4 XS	-	-	-	-	-	85	60	38	27	18
4 XXS	-	123	110	101	90	61	44	28	20	13
	15000	13000	11000	10000	9000	8000	7000	5000	3000	1000
2-1/2" 0.750W	-	31	29	29	28	27	25	23	16	5
2-1/2" 0.875W	22	21	20	19	19	18	17	15	11	3
2-1/2" 1.000W	13	13	12	12	11	11	10	9	7	2