

C&C 44

Sailboat Specifications

Hull Type:	Fin w/spade rudder
Rigging Type:	Masthead Sloop
LOA:	44.17 ft / 13.46 m
LOD:	
LWL:	35.25 ft / 10.74 m
S.A. (reported):	924.00 ft ² / 85.84 m ²
Beam:	13.25 ft / 4.04 m
Beam WL:	
Displacement:	20,906.00 lb / 9,483 kg
Ballast:	9,850.00 lb / 4,468 kg
Max Draft:	8.25 ft / 2.51 m
Construction:	FG
Ballast Type:	Lead
First Built:	1985
Last Built:	1991
Builder:	C&C Yachts
Designer:	C&C Design Robert Ball

Auxiliary Power/Tanks (orig. equip.)

Make:	Yanmar
Type:	Diesel
Fuel:	40 gals / 151 L

Accomodations

Water:	100 gals / 379 L
---------------	------------------

Sailboat Calculations

S.A. / Displ.:	19.56
Bal. / Displ.:	47.12
Disp: / Len:	213.08
Comfort Ratio:	27.28
Capsize Screening Formula:	1.93
S#:	2.83
Hull Speed:	7.96 kn
Pounds/Inch Immersion:	1,668.87 pounds/inch

Rig and Sail Particulars

I:	59.00 ft / 17.98 m
J:	17.50 ft / 5.33 m
P:	51.75 ft / 15.77 m
E:	15.75 ft / 4.80 m
S.A. Fore:	516.25 ft ² / 47.96 m ²
S.A. Main:	407.53 ft ² / 37.86 m ²
S.A. Total (100% Fore + Main Triangles):	923.78 ft ² / 85.82 m ²
S.A./Displ. (calc.):	19.55
Est. Forestay Length:	61.54 ft / 18.76 m

Sailboat Organizations

Designer:	C&C Design Robert Ball
Builders:	C&C Yachts

Additional Notes

The first C&C 44 was built in Canada, the rest at C&C's Middletown, RI (USA) plant. Available with many different ballast-keel combinations and rig options.

Keel/centerboard vers.: BU - 5.5'; BD - 8.5'.