






ALFRA HOLE PUNCHER® – SPECIAL FORMS

- All hole puncher are fitted with side ejection for the waste piece.
No jamming in the die
- The hole puncher are supplied in heavy duty, practical plastic cases




Size in mm	Max. Material thickness in mm (S235)	For use in	pre-drilling in mm					
				incl. 1 - 4	draw bolt	counternut or bridge	Ball bearing pressure nut	Adapter for hydraulic

Hole punchers special forms – for sheet steel (S235)

					Prod.-No.				
 Ø 22.5 with 3.2 mm lug	2.0	●	●	14	01420	01333			
 Ø 22.5 2-sided flattened to 18.5 mm	2.0	●	●	14	01421		01351		
 Ø 22.5 4-sided flattened to 20.1 mm	2.0	●	●	14	01422	01347			01352
 33.3 x 17.0 x 10.0 for profile cylinder	2.0	●	●	14	01423				
 Ø 16.3 4-sided flattened to 14.1 mm	1.75	●	●	11	01427	01348	01355		

Hole punchers special forms – for stainless steel (VA)

 Ø 22.5 with 3.2 mm lug	2.0	●	●	14	014201	01333	01351	01352	01353
---	-----	---	---	----	---------------	-------	-------	-------	-------