



ALFRA ROTABEST® – RB 50 B

B-LINE



MADE IN GERMANY

		
Up to Ø50 mm	Ø10 - 40 mm	Up to Ø20 mm
RB 50 B		
Core drill dimensions	Ø 12.0 - 50.0 mm	
Cutting depth	50.0 mm	
Twist drill	Ø 1.0 to 16.0 mm with quick-release chuck MT2 up to Ø 20.0 mm with MT 2 DIN 345 direct	
Counterboring	Ø 10.0 - 40.0 mm	
Tapping	with tapping attachment M3 - M20	
Arbors	MT2	
Stroke	190 mm	
Height adjustment	100 mm	
2-speed gearbox Load speed	1. Step 250 rpm 2. Step 450 rpm	
Power consumption	1,200 W	
Voltage	230 V 50/60 Hz 110 V 50/60 Hz	
Magnetic adhesion strength	12,000 N	
Tool force (10 mm)	3,500 N	
Magnetic base	92 x 220 mm	
Weight	15.0 kg	
Motor		
Oil bath gearbox	✓	
Slides		
Infinitely adjustable	✓	
Self-adjusting guide	✓	
Operation		
Soft-touch grips	✓	
Ergonomic switch keyboard	✓	
Cable length 5 m	✓	
Magnet		
Metal rings	✓	
Performance and weight optimisation	✓	
Made in Germany		
Scope of delivery		
<ul style="list-style-type: none">• Metal core drilling machine RB 50 B• Coolant device• MT2 tool holder with internal cooling• Carrying case• Drill spray• Seat belt• Operating Instructions• incl. 1 core drill free		

Prod.-No.

ALFRA Rotabest® RB 50 B	230 Volt	18451
ALFRA Rotabest® RB 50 B	110 Volt	18451.110