




**Clamping Arm with Hydraulic Short Stroke Clamping Cylinder**

- 8 mm hub
- Large scale pressure piece for secure clamping on both sides of the saw blade
- Hand crank for pre-adjustment
- Flexible in material measurement, especially within wide limits



**Rotary Table for Mitre Cuts**

- Easy, manual adjustment
- Pivoting range 180°
- Manually controlled motorized setting of the mitre angle (optional)



**Schnittgeschwindigkeit  
Cutting Speed**

1950/3900 m/min.

**High Cutting Capacity**

- Adaptable to the material
- Two cutting speeds as standard

Technical Data		SKL 450 E	SKL 450 H	SKL 450 NA
Sawblade	Ø mm	450	450	450
Drive performance	kW	3,7/4,7	3,7/4,7 resp. 4,7/6,3	3,7/4,7 resp. 4,7/6,3
Cutting speed	m/min	1.950/3.900	1.950/3.900	1.950/3.900
Feedrate	mm/min	0-3000	0-3.000	0-3.000
Rapid advance/ return movement	mm/min	4.500	4.500	4.500
Machine Weight	kg	680	680	1.480
Working range	mm	160	160	160
Working range Square	mm	145x145	145x145	320x50
Working range Flatmaterial	mm	320x50	320x50	145x145
Working range Roundmaterial	mm	160	160	160
Mitre range		0°/90°/0°	0°/90°/0°	0°/90°/0°
Tools		Carbide Tools	Carbide Tools	Carbide Tools