



## RB 50 B RL-E

Core drill dimensions	Ø 12.0 - 50.0 mm
Cutting depth	50.0 mm
Twist drill	Ø 1.0 to 16.0 mm with quick-release chuck MT2 up to Ø 20.0 mm with MT 2 DIN 345 direct
Counterboring	Ø 10.0 - 40.0 mm
Tapping	with tapping chucks: M3 - M14 with tapping attachment M3 - M20
Arbors	MT2
Stroke	170 mm
Height adjustment	100 mm
2-speed gearbox	right / left 1. Step 100 - 250 rpm 2. Step 180 - 450 rpm
Power consumption	1,200 W
Voltage	230 V 50/60 Hz 110 V 50/60 Hz
Magnetic adhesion strength	16,000 N
Tool force (10 mm)	3,800 N
Magnetic base	92 x 238 mm
Weight	16.0 kg

Motor	
Right/left run	✓
Oil bath gearbox	✓
Slides	
Infinitely adjustable	✓
Operation	
Soft-touch grips	✓
Ergonomic switch keyboard	✓
Magnet	
Metal rings	✓
Made in Germany	✓

Scope of delivery	
<ul style="list-style-type: none"> <li>• Metal core drilling machine RB 50 B RL-E</li> <li>• Coolant device</li> <li>• MT2 tool holder with internal cooling</li> <li>• Quick-release chuck for twist drills</li> <li>• Carrying case</li> <li>• Drill spray</li> <li>• Chip hook</li> <li>• Seat belt</li> <li>• Operating Instructions</li> <li>• <b>incl. 1 core drill free</b></li> </ul>	



**MADE IN GERMANY**



**Prod.-No.**

ALFRA Rotabest® RB 50 B RL-E	230 Volt	18612
ALFRA Rotabest® RB 50 B RL-E	110 Volt	18612.110