



## RB 35/50 B PICCOLO

Core drill dimensions	Ø 12.0 - 35.0 mm
Cutting depth	50.0 mm
Twist drill	Ø 1.0 - 13.0 mm
Counterboring	Ø 10.0 - 40.0 mm
Arbors	19 mm Weldon shank
Stroke	129 mm
Height adjustment	86 mm
Gearbox – on-load speed	450 U/min,
Power consumption	1,100 W
Voltage	230 V 50/60 Hz 110 V 50/60 Hz
Magnetic adhesion strength	10,000 N
Tool force (10 mm)	2,100 N
Magnetic base	70 x 185 mm
Weight	11.5 kg

<b>Motor</b>	
Grease drive	✓
<b>Slides</b>	
Infinitely adjustable	✓
Self-adjusting guide	✓
<b>Operation</b>	
Soft-touch grips	✓
Ergonomic switch keyboard	✓
Cable length 5 m	✓
<b>Magnet</b>	
Metal rings	✓
Performance and weight optimisation	✓

Made in Germany ✓

<b>Scope of delivery</b>	
<ul style="list-style-type: none"> <li>• Metal core drilling machine RB 35/50 B Piccolo</li> <li>• Coolant device</li> <li>• Carrying case</li> <li>• Seat belt</li> <li>• Operating Instructions</li> </ul>	



MADE IN GERMANY



**Prod.-No.**

ALFRA Rotabest® RB 35/50 B Piccolo 230 Volt

18401

ALFRA Rotabest® RB 35/50 B Piccolo 110 Volt

18401.110