

## **B-LINE**





Up to 1935 mm 1	)10 - 40 mm	Up to Ø 13 mm		
R	B 35 B			
Core drill dimensions	Ø 12.0 - 35.0 mm			
Cutting depth	50.0 mm			
Twist drill	Ø 1.0 - 13.0 mm DIN 1897 short			
Counterboring	Ø 10.0 - 40.0 mm			
Arbors	19 mm Weldon shank			
Stroke	120 mm			
Gearbox - on-load speed	4	50 rpm		
Power consumption	1	,100 W		
Voltage	230 V 50/60 Hz 110 V 50/60 Hz			
Magnetic adhesion strength	10,000 N			
Tool force (10 mm)	2,100 N			
Magnetic base	70 x 185 mm			
Weight	10.6 kg			
Slide				
Self-adjusting guide		V		
Operation				
Soft-touch grips		V		
Ergonomic switch keyboard		<b>~</b>		
Cable length 5 m		V		
Magnet				
Metal rings		<b>V</b>		
Performance and weight optimisation		V		
Made in Germany		V		
Scope of delivery				

- Metal core drilling machine RB 35 B
  Coolant device
  Carrying case
  Seat belt
  Operating Instructions
  incl. 1 core drill free

## Prod.-No.

ALFRA Rotabest® RB 35 B	230 Volt	18400
ALFRA Rotabest® RB 35 B	110 Volt	18400.110