

T-200 Series Compactors |

- Advance-warning light
- Fluid-filled pressure gauge
- Oil heater
- Odour control system
- Open hopper (for top or loading dock)
- Fully enclosed hopper with door
- Through the wall installation kits
- Walk-on or drive-on decks
- Safety gate
- Hydraulic cart-dump systems

Mechanical Specifications

	T200	T200HD	T200XHD	T200X
Charge Chamber Volume	2	2	2	2
Charge Chamber Opening Size	42" x 60"	42" x 60"	42" x 60"	42" x 60"
Ram Face Size	27" x 60"	27" x 60"	27" x 60"	27" x 60"
Ram Penetration	13"	13"	13"	13"
Compaction Force Normal	56,500 lbs	76,930 lbs	113,000 lbs	50,240 lbs
Compaction Force Maximum	64,975 lbs	88,470 lbs	129,950 lbs	55,260 lbs
Cycle Time	63 seconds	63 seconds	73 seconds	63 seconds
System Pressure Normal	2000 psi	2000 psi	2000 psi	2000 psi
System Pressure Maximum	2200 psi	2200 psi	2200 psi	2200 psi
Pump Capacity	10 gpm	10 gpm	10 gpm	10 gpm
Motor Size	10 hp	15 hp	15 hp	10 hp
Cylinder Size	6"0 x 54"	7"0 x 54"	2 x 6"0 x 54"	2 x 4"0 x 42"
Cylinder Type	Double Acting	Double Acting	Double Acting	Double Acting
Ram Face Pressure Normal	34.2 psi	46.6 psi	68.5 psi	30.5 psi
Ram Face Pressure Maximum	39.4 psi	53.6 psi	78.8 psi	33.4 psi
Oil Tank Capacity	20 gal	25 gal	75 gal	20 gal
Shipping Weight	4,100 lbs	5,100 lbs	7,500 lbs	4,100 lbs

Electrical Specifications

Control System	110 volt 60 cycle powered by step-down transformer
Control Panel	Fully wired. Keyed start button, emergency stop, full light, reset button, PLC, current sensor
Power	208/230/575 Volt, 3 Phase 60 Cycle