


PULPERV-Belt Drive
Certification SheetVOITH, INC.
2620 E. Glendale
Appleton, WI 54915
Tel (414) 731-7724
Telefax (414) 731-0240

IDENTIFICATION	CUSTOMER <u>VOITH, INC.</u>	CUST. DESIGNATION <u>HD-6 HIGH CONSISTENCY</u>
	ADDRESS (ORDER) <u>APPLETON, WI</u>	
	ADDRESS (INSTALL) <u>SAME</u>	TYPE/SERIAL NO. (S)* <u>3145</u>
	CUST. ORDER NO. <u>ACUM1002</u>	VOITH JOB NO. <u>Y91-7777</u>
	CUST. EQUIP. NO. _____	ORDER DATE <u>1-1-91</u>
	CONTROLS BY <u>VOITH</u>	CONTROLS SERIAL NO.* _____
CERTIFIED BY <u></u>	TITLE <u>MANAGER OF ENGINEERING, S.P. DIV.</u>	
ROBERT J. MATZ, P.E.		
APPLICATION	INSTALLATION DWG. <u>D23-130013</u>	STOCK <u>ALL</u>
	STOCK CONSISTENCY <u>12-18% BD</u>	pH <u>5 - 10</u> TEMP <u>78 - 150° F</u> BATCH _____
	TANK BY <u>VOITH</u>	DIM: <u>98.62 I.D.</u> HEIGHT <u>96.00 OAH</u> MAT'L <u>316/MS</u>
	CAP AT OPER. LEVEL <u>(60 CU M) 212</u>	CU.FT. IMPELLER RPM <u>207</u>
	EXTRACTION HOLE SIZE <u>N/A</u>	BLADE TYPE <u>HD-6</u>
	DEFIBERING RING <u>N/A</u>	EXTRACTION: <u>WITHOUT</u>
MAT'L	PULPING UNIT <u>316/MS</u> EXTRACTION PLATES <u>316</u> EXTRACTION CHAMBER <u>316</u>	
	DEFIBERING RINGS <u>N/A</u>	
DRIVE	DRIVE BY <u>VOITH</u> POWERBAND NO. <u>2</u> SIZE <u>3/8VX3150</u> C.D. <u>84.10</u>	
	MOTOR SHEAVE <u>6 GR 8 V 17.00</u> O.D. BORE _____ KW _____	
	DRIVEN SHEAVE <u>6 GR 8 V 71.00</u> O.D. BORE <u>5.000</u> KW <u>1.250 X 0.625</u>	
	BELT PULL ON MOTOR _____	
MTR	MOTOR BY <u>VOITH</u> FRAME SIZE _____ HP <u>200</u> RPM <u>900</u>	
OPTIONS	<u>FURNISHED ONLY IF MARKED</u>	
	☐ CONTROL PANEL	☒ BELT GUARD ☐ STEAM VALVES
	☒ ADJ. MOTOR BASE	☒ <u>16</u> " DUMP VALVE ☐ _____ " JUNK TRAP
	☐ TANK MANWAY	☒ TANK HOOD
REMARKS	*ALWAYS SPECIFY UNIT SERIAL NO. WHEN ORDERING SPARE PARTS	