



RIG NO. 6- INVENTORY OF EQUIPMENT



WELLCONTROL: 13-5/8" 5,000 psi
annular 13-5/8" 5,000 psi double ram
210 Gallon 10,000 psi Choke Manifold

ACCUMULATOR: NL Shaffer 7 Station with Remote Panel

MUDSYSTEM: TWO (2) Two Tanks, 800 bbl capacity

SHALE SHAKERS-THREE (3) Two Brandt King Cobra Dual
Motion shale shakers Atmospheric Degasser

GENERATORS: Four (4) Caterpillar 3512 engines SCR/MCC power
control house 4 x 4 with Top Drive Feeder

SCR HOUSE: Omron 4x4

BLOCK/HOOK: Ideco 480 ton block

ROTARYTABLE: Ideco 27-1/2"

WATER TANK: 500 BBL

FUEL TANK: 10,000 Gallon

DRILLERS DOGHOUSE:

AUXILIARY EQUIPMENT: Ingersoll Rand air hoists Iron
Roughneck Automatic Catwalk

INSTRUMENTATION: WEIGHT INDICATOR, W/TONG LINE
PULL, PUMP PRESSURE & ROTARY TORQUE GAUGES,
TYPE "D"

5,000 PSI MUD PRESSURE GAUGE

DRAWWORKS: National 110 E, 1500hp
Baylor 6032 Aux Brake 1-3/8" drill line

ENGINES: Powered by Two (2) 800 HP GE 752 traction
motors

MAST: Superior 142'
768,000 # static hook load

SUBSTRUCTURE: Box on Box 25' x 34' x 50'
25" KB height
High Density Walking System

AC TOP DRIVE: Canrig Model 1250AC, 500-ton
51,000 FT/LBS of Continuous Torque

MUD PUMPS: Three (3) Bomco FB-1600, 1600 hp triplex
Powered by two 800HP traction motors
Rated at 7,500 psi

\$3,950,000.00
Wisco Victoria, Tx