


# Single end Tenoners 5000-5500



#### FEATURES:

The 2 horizontal heads, 114 mm (41/2") wide will cut tenous of 114 mm  $(4^1/2'')$  wide on the first pass or 152 mm (6'') on a double pass. The 2 vertical heads will shape the tenon. Each vertical head is fitted with one horizontal head. It could be adjusted simultaneously in height. Only the upper horizontal head is adjustable in

A cut-off saw cuts the tenon to the correct length.

The table slides on 2 rails (one "V" shaped) with 4 hardened steel rollers mounted on sealed bearings.

Safety guards are provided over all the cutting knives and

## NO. 5500 SPECIFIC FEATURES:

This model shows the same features and technical data as the 5000 but also offers these extra advantages:

The 2 motors supplied (2 H.P. for horizontal heads and 1 H.P. for vertical heads and cut-off saw) provides high efficiency by allowing working only with either vertical or horizontal heads.

The magnetic starters are supplied with push-buttons stations located in fron of machine under a safety cover.

A higher rigidity is obtained by a heavier cast iron closed base.

### MACHINE DATA:

Max length of tenon: 152 mm (6" Max. width of tenon: 330 mm (13")

Vertical heads, 3 knives: 100 mm  $\times$  25.4 mm (3<sup>15</sup>/<sub>16</sub>"  $\times$  1")

Horizontal heads, 2 knives; 114 mm (41/2"

Table dimensions: 723 mm  $\times$  406 mm (28 $^{1}/_{2}$ "  $\times$  16")

Cut-off saw: diameter: 178 mm (7") max. thickness: 63 mm (21/2")

horizontal adjustment: 152 mm (6")

Recommended working speed of tools: 3800 rpm Motor rating: No. 5000: 3 H.P. at 1725 rpm No. 5500 2 and 1 H.P.

Floor space: No. 5000: 1524 mm × 1117 mm (60" × 44") No. 5500: 1651 mm × 1168 mm (65" × 46")

# STANDARD EQUIPMENT:

No. 5000: Pulleys, belts, knives.

Operation and maintenance manual.

No. 5500: Pulleys, belts, knives. Motors (T.E.F.C.).

Magnetic starters. Operation and maintenance manual.

#### SHIPPING:

Crate dimensions:

No. 5000: 1524 mm  $\times$  1117 mm  $\times$  1422 mm (60"  $\times$  44"  $\times$  56") No. 5500: 1651 mm  $\times$  1168 mm  $\times$  1346 mm (65"  $\times$  46"  $\times$  53")

Weight: No. 5000: 431 kg (950 lb)

5500: 522 kg (1150 lb)

No. 5000: 2.42 m3 (85.5 ft3)

5500: 2.57 m3 (91 ft")

C.S.A. approved

