



VITRA Multi-tool- carrier

*A versatile and
ingenious Danish
design
Ready for action in
summer and winter*

The Vitra MTC has been designed in close cooperation with the end-user. And this shows in the final result of this unique machine:

- Excellent control and comfort for the driver
- Easy exchange of parts for a fast change in type of operations
- Very versatile because of the various attachment for various activities on the terrain
- Low maintenance costs
- Good looks

In short a machine to fall in love with!



we help you to keep our environment clean

Daltonweg 2 3208 KV Zwijndrecht t: +31. 78- 6 10 80 10
i: www.sweepingmachines.com e: info@sweepingmachines.com



Ready for action in summer and winter

Because of the many tools and attachments the Vitra MTC can be used for nearly all operations on the terrain, from weed brushing to street-cleaning, mowing, salt spreading and even snowploughing.

The handy design enables you to change the various attachments tools very easily. The vitra MTC is the yearround at your service.



Superior driving and handling

All Vitra MTC's have a permanent 4 wheel drive and a central differential lock. This results in superior offroad driving characteristics. In combination with the sof track system the VITRA is very fit for grassy surfaces.

Another example of the design is the tracking: de rear wheels always follow the trail of the front wheels.

The same width on front and backside assures the driver to take him through narrow passages without exceptional steering.



The atriculated steering makes the Vitra MTC very maneuverable. The inner turning circle measures just 80 to 92 cm, leaving all other multitoolcarriers way behind.



Low maintenance costs

All parts which are important for maintenance, such as air and oil filters and measuring points for liquids are easily accessible.

Combined with the solidity of the machine this results in very low maintenance costs and a very trustworthy character.

we help you to keep our environment clean



Daltonweg 2 3208 KV Zwijndrecht t: 078- 6 10 80 10
i: www.sweepingmachines.com e: info@sweepingmachines.com



Focus on the driver



Vier type machines

De Vitra MTC kan geleverd worden met motoren van 29 pk tot 60 pk. Voor ieder toepassingsgebied verschaffen de Kubota diesel voldoende vermogen. De twee grootste motoren zijn zelfs uitgerust met een turbo charger voor het zwaarste werk.



Financial en operationale lease

Door de grote betrouwbaarheid en de lage onderhoudskosten is de Vitra MTC bij uitstek geschikt voor zowel financiële als operationele lease.



we help you to keep our environment clean

Daltonweg 2 3208 KV Zwijndrecht
i: www.sweepingmachines.com

t: 078- 6 10 80 10
e: info@sweepingmachines.com



Technische gegevens

	2030	2037	2045	2060
Motor	Kubota	Kubota	Kubota	Kubota
Cilinders	3	4	4 + turbo	4 + turbo
Cilinderinhoud	1.000	1.498	1.498	1.998
Vermogen	21 pk / 29 Kw	37 pk / 27 Kw	45 pk / 35 Kw	60 pk / 44 Kw
Koelsysteem	Vloeistof	Vloeistof	Vloeistof	Vloeistof
Brandstoftank	24 liter	46 liter	46 liter	46 liter

Transmissie

Wielmotoren	4 x	4 x	4 x	4 x
Snelheid	0 – 24 km/ uur	0 – 30 km/ uur	0 – 35 km/ uur	0 – 38 km/ uur
Aandrijving	4 x 4	4 x 4	4 x 4	4 x 4

Hydraulica

T.b.v. rijsysteem:

Capaciteit	40 ltr / 180 bar	60 ltr / 200 bar	60 ltr / 220 bar	70 ltr / 250 bar
Omdraaibaar	Optioneel	Standaard	Standaard	Standaard

T.b.v. componenten:

Capaciteit	14 ltr / 200 bar	20 ltr / 140 bar	20 ltr / 140 bar	20 ltr / 160 bar
Hydraulica aansluitingen	Voor 1	Voor 2	Voor 2	Voor 2
(uitbreiding optioneel)	Achter 1	Achter 1	Achter 1	Achter 1

Elektrisch systeem

Dynamo	40 Ampère	60 Ampère	60 Ampère	60 Ampère
Wegverlichting	Standaard	Standaard	Standaard	Standaard
Zwaailicht	1 x standaard	1 x standaard	1 x standaard	1 x standaard
Aansluiting 7 polig	Optioneel	Standaard	Standaard	Standaard
Radio / CD	Optioneel	Standaard	Standaard	Standaard

Afmetingen en gewichten

Lengte	2.680 mm	2.850 mm	2.850 mm	2.850 mm
Max. breedte	1.050 mm	1.090 mm	1.180 mm	1.255 mm
Hoogte	2.000 mm	2.000 mm	2.010 mm	2.075 mm
Bodemvrijheid	135 mm	135 mm	145 mm	200 mm
Bin. draaicirkel	800 mm	925 mm	925 mm	1.000 mm
Gewicht in kg	1.020 kg	1.180 kg	1.220 kg	1.320 kg