



JTM-4VS Mill With ACU-RITE 203 DRO With X and Y-Axis Powerfeeds

Product Images



Short Description

JTM-4VS Mill With ACU-RITE 203 DRO With X and Y-Axis Powerfeeds

Additional Information

Stock Number	JT9-690098-4
Collet Capacity	1/8 - 7/8
Distance Spindle to Column (Max.) (In.)	19
Max Distance Spindle to Table (In.)	17-1/2
Model Number	JTM-4VS
Motor (HP)	3 HP, 230/460V, 3Ph
Number of Axis	2
Overall Dimensions (L x W x H) (In.)	66 x 63 x 85
Powerfeed	X and Y-Axis
Prop 65	Cancer and Reproductive Harm
Quill Diameter (In.)	3-3/8
Quill Down Feed Rates (IPR)	.0015 - .003 - .006
Range of Spindle Speeds (RPM)	60 - 4,200
Spindle Taper (In. x TPI)	R-8
Spindle Travel (In.)	5
Style (Type)	Variable Speed R8
T-Slot Centers (In.)	2-1/2
Table Cross Travel (In.)	12
Table Longitudinal Travel (In.)	34
Table Longitudinal Travel With Powerfeed (In.)	28-3/4
Table Size (L x W) (In.)	9 x 49
Travel of Knee (In.)	14-1/2
Travel of Ram (In.)	13-3/8
Warranty	2 Year

Work Table Weight Capacity (Lbs.)	660
Gross Weight	2420.0
Net weight	2420.0

