



423-S

Closed-End Automatic Horizontal Baler

<i>Overall Length</i>	157-1/8"
<i>Overall Width</i>	39-3/4"
<i>Overall Height</i>	66-3/8"
<i>Nominal Hopper Size</i>	30 wide x 40 long
<i>Product Bale Size</i>	30 wide x 30 deep x 42
<i>Number of Bale Ties</i>	3
<i>Hydraulic Reservoir Capacity</i>	26 gal
<i>Cycle (in seconds)</i>	15
<i>Ram Face Pressure:</i>	20.9 psi
<i>Ram Thrust</i>	18,800 lbs.
<i>Hydraulic System Pressure</i>	1500 psi
<i>Pump Capacity</i>	16.5 gpm
<i>Main Cylinder</i>	4" bore x 46" stroke
<i>Main Motor Size</i>	15 HP, 208-220/440-550 Volt, 3 Phase, 60 Cycle, T.E.F.C.
<i>Total Press Weight</i>	3,700 lbs. (approx.)
<i>Reference Layout Drawing</i>	A223-A34

Standard Features

- * Pre-wired Standard Magnetic Starters
- * Pushbutton Workstation
- * T.E.F.C. Motors
- * Full Oil Reservoir -- Ready to Run
- * Access Door on In feed Chute with Safety Switch (Automatic Units)
- * 5 feet of Discharge Roller Conveyor Included
- * Option of Left or Right-hand Controls
- * 30" wide X 40" long Feed Opening
- * UL Listed Control Panel
- * NEMA 12 Dust-tight Electrical Cabinet
- * Solid Bridge Ring
- * Solid End Ring
- * Over the center door lock
- * Heavy duty door hinges with 1-1/2" pins