

PRODUCT INFORMATION

Product Func : Paper Roll Clamp **Size/Gen:** 60G
Attachment: 360 Degree Revolving
Mounting Size: Class III, Two Degree
Mounting Type: Bolt On
Arm: Powered Long Arm and Fixed Short Arm
Pad Height: 41.9 inches
Pad Width: 9.8 inches
Pad Facing: Bolt on Smooth Black Non Marking Rubber (65 Durometer)
PN 6016389
To Handle Minimum Roll Diameter: 20 inches
To Handle Maximum Roll Diameter: 51 inches
Minimum Truck Carriage Width: 32 inches



Image shown for illustrative purposes only

SPECIFICATIONS

Capacity:	6000 lbs
Load Center:	25.5 in.
Estimated Weight:	1795 lbs
ET:	6.9 in.
HCG:	10.5 in.
VCG:	17.6 in.
Max Lateral Offset:	in.
Lateral CG at Max Lateral Offset:	in.

HYDRAULIC

Max Pressure:	2600 psi
Recommended Flow:	10 gpm
Minimum Flow:	5 gpm
Maximum Flow:	15 gpm
Required Truck Aux Functions:	2

Any custom order that is over 2 weeks past entry or any standard order with a requested ship date more than 4 months past our current lead time could be subject to price increase and/or cancellation charge.