

New Attachment

Quote: 89418 Rev. 5 Date: SEP 13, 2010

Cascade Part No: 60G-RCF-164

PRODUCT INFORMATION

Product Func: Paper Roll Clamp Size/Gen: 60G

Attachment: 360 Degree Revolving Mounting Size: Class III, Two Degree

Mounting Type: Bolt On

Arm: Powered Long Arm and Fixed Short Arm

Arm: Cylinder Rod End Anchor Pins Thru Both Side Plates

Pad Height: 41.9 inches Pad Width: 9.8 inches

Pad Facing: Bolt on Black Rubber (65 Durometer) on Long Arm Only

Pad Protectors

To Handle Minimum Roll Diameter: 20 inches To Handle Maximum Roll Diameter: 51 inches Minimum Truck Carriage Width: 32 inches

Option#1- 2 Function 10gpm Flow Control W/P-Relief....List Price

\$1,210

Option#2- Return to Tank Line KitList Price \$160

Option#3- HYG Specific Install Kit (part#T.B.D.)....List Price \$155



Image shown for illustrative purposes only

SPECIFICATIONS			HYDRAULIC		
Capacity:	6000	lbs	Max Pressure:	2600	psi
Load Center:	25.5	in.	Recommended Flow:	10	gpm
Estimated Weight:	1805	lbs	Minimum Flow:	5	gpm
ET:	6.9	in.	Maximum Flow:	15	gpm
HCG:	10.9	in.	Required Truck Aux Functions:	2	
VCG:	17.6	in.			

Any custom order that is over 2 weeks past entry or any standard order with a requested ship date more than 4 months past our current lead time could be subject to price increase and/or cancellation charge.