



service unit combination MSB4

Part number: 531029

☆ Core product range

For manifold assembly, with G thread.

FESTO



Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Size	4
Series	MS
Type of actuation	electrical manual pneumatic
Actuator lock	Rotary knob with integrated lock
Assembly position	Any Vertical +/- 5°
Grade of filtration	0,01 ... 40 µm
Condensate drain	fully automatic manual rotary semi-automatic
Design structure	Branching module Active carbon filter Pressure regulator with gauge Start-up valve On/off valve Fibre filter Filter regulator with pressure gauge Filter regulator without pressure gauge Membrane dryer proportional standard mist lubricator Sintered filter with centrifugal separator With non-return function
Controller function	Output pressure constant with initial pressure compensation with secondary exhaust with return flow
Bowl guard	Plastic guard
Differential pressure display	Visual indicator with pressure sensor
Pressure gauge	with pressure sensor with pressure gauge
Operating pressure	1,5 ... 14 bar
Pressure regulation range	1 ... 12 bar
Standard nominal flow rate	800 ... 1.400 l/min
Characteristic coil data	110 V AC: 50/60 Hz, pick-up power 3 VA, holding power 2.4 VA 230 V AC: 50/60 Hz, pick-up power 3 VA, holding power 2.4 VA 24 V DC: 1.5 W 24 V DC: 1.8 W
ATEX category Gas	II 2G II 3G

Feature	Value
ATEX category Dust	II 2D II 3D
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
CE mark (see declaration of conformity)	to EU directive for EMC to EU directive explosion protection (ATEX) to EU directive low-voltage devices
Corrosion resistance classification CRC	2 - Moderate corrosion stress
Storage temperature	-10 ... 60 °C
Medium temperature	-10 ... 60 °C
Ambient temperature	-10 ... 60 °C
Authorisation	c UL us - Recognized (OL)
Mounting type	with accessories
Pneumatic connection, port 1	G1/8 G1/4
Pneumatic connection, port 2	G1/8 G1/4
Pneumatic connection, port 3	G1/4
Materials information, housing	Aluminium die cast
Materials information for bowl	PC