

ABB's website uses cookies. By staying here you are agreeing to our use of cookies. → [Learn more](#)

I agree

You can view this page in: [E](#)[D](#)[S](#)[F](#)[C](#)[D](#)[E](#)[E](#)[F](#)[H](#)[I](#)[J](#)[K](#)[N](#)[N](#)[P](#)[P](#)[R](#)[S](#)[T](#)[Z](#)[H](#)

## Detailed information for: F202 A-25/0,03

This page contains technical data sheet, documents library and links to offering related to this product. [Print...](#)  
If you require any other information, please contact us using form located at the bottom of the page. [Print to Pdf...](#)

Data Sheet Downloads

### F202 A-25/0,03

#### General Information

Extended Product Type:	F202 A-25/0,03
Product ID:	2CSF202101R1250
EAN:	8012542782506
Catalog Description:	F202 A-25/0,03 Residual Current Circuit Breaker
Long Description:	The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications.



#### Categories

Products » [Low Voltage Products and Systems](#) » [Modular DIN Rail Products](#) » [Residual Current Devices RCDs](#) » [Residual Current Devices RCDs](#)



#### Technical

Standards:	IEC/EN 61008 UL 1053
Operating Characteristic:	Instantaneous
Type of Residual Current:	A type
Rated Residual Current:	30 mA
Rated Current (I <sub>n</sub> ):	25 A
Number of Poles:	2
Power Loss:	at Rated Operating Conditions per Pole 1 W
Rated Voltage (U <sub>i</sub> ):	230/400 V
Rated Frequency (f):	50/60 Hz
Ambient Air Temperature:	Operation -25...55 °C
Connecting Capacity:	Busbar 10 mm <sup>2</sup> Rigid 25 ...25 mm <sup>2</sup> Flexible 25 ...25 mm <sup>2</sup>
Degree of Protection:	IP2X
Electrical Endurance:	10000 cycle
Mounting Type:	DIN rail
Object Classification Code:	Q
Pollution Degree:	2
Rated Conditional Short-Circuit Current (I <sub>nc</sub> ):	10 kA
Rated Insulation Voltage (U <sub>i</sub> ):	500 V
Rated Operational Voltage:	230 V AC
Width in Number of Modular Spacings:	2

#### Environmental

Ambient Air Temperature:	Operation -25...55 °C
RoHS Status:	Following EU Directive 2011/65/EU

#### Technical UL/CSA

Maximum Operating Voltage UL/CSA:	277 V AC
-----------------------------------	----------

#### Dimensions

Product Net Width:	0.035 m
Product Net Height:	0.085 m
Product Net Depth / Length:	0.069 m
Product Net Weight:	0.200 kg

#### Container Information

Package Level 1 Units:	box 1 piece
Package Level 1 Width:	80 mm
Package Level 1 Height:	41 mm
Package Level 1 Depth / Length:	94 mm
Package Level 1 Gross Weight:	0.235 kg
Package Level 1 EAN:	8012542782506
Package Level 2 Units:	crate 6 piece
Package Level 2 Width:	246 mm
Package Level 2 Height:	94 mm
Package Level 2 Depth / Length:	80 mm

#### Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363030
E-Number (Sweden):	2160114
E-Number (Finland):	3259225

#### Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	<a href="#">9AKK106713A5602</a>
Environmental Information:	<a href="#">Refer to RoHS</a>
Instructions and Manuals:	<a href="#">9AKK107991A6127</a>
RoHS Information:	<a href="#">2CSC423001K2702</a>

#### Popular Downloads

Data Sheet, Technical Information:	<a href="#">9AKK107991A8329</a>
Instructions and Manuals:	<a href="#">9AKK107991A6127</a>

#### Classifications

Object Classification Code:	Q
ETIM 4:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 5:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 6:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 7:	EC000003 - Residual current circuit breaker (RCCB)

### Contact us

Submit your inquiry and we will contact you

CONTACT US

Or contact your [ABB Contact Center](#)

POPULAR LINKS

FOLLOW US



CURRENT SHARE PRICE

New York

36.62 USD

-1.05% at 2021-07-30, 16:00