

Appendix B

UCAP-150 Technical Specifications

Size of containers

Diameter: Min: ¾" (18 mm) Max: 6 ¼" (158 mm)

Height: Single belt: Min: 2 ½" (63 mm) Max: 5" (127 mm)
Double belt: Min: 2" (51 mm) Max: 12" (305 mm)

Format: Round, rectangular, oval

Size of caps

Diameter: Min: ¾" (18 mm) Max: 3" (75mm)
Up to 5" (127 mm) on request

Type: Screw cap, snap cap, child-proof cap (in plastic or metal)

Clearance between tightening disks: Max: 6" (150 mm)

Overall dimensions of the machine (See Layouts with options)

Length: 3 ft (0.91 m)

Width: 3 ft (0.91 m)

Height: 5 ft (1.52 m)

Cap elevator with air reject

Cap diameter: Min: ¾" (18 mm) Max: 3" (75 mm) exterior
Up to 4 ¼" (110 mm) exterior on request

Output: 200 – 220 CPM (33/45 cap type 400 plastic)
200 – 300 CPM (33/45 child-proof in plastic)
200 – 220 CPM (33/45 mm cap type 400 metal)

Hopper capacity: 3 cu. ft. (0.08 cu. m)

Air supply: Please refer to rating plate on machine.