

SPEED BINDING MACHINE

ACCURATE WIRE-O® DOCUMENT FINISHER FOR ON DEMAND APPLICATIONS

At 500-1000 books per hour, the semi-automatic WIRE-O® BIND 3500 is fast, yet simple to operate with all size and formats stups instantly adjustable by user-friendly "touch screen" electronic controls.

> The versatile WIRE-O® BIND 3500 is designed to work alongside the highly successful Alpha-Doc® and Docu-Punch® automatic punching machines, accurately finishing a wide variety of documents,

Wire-O[®] sizes up to 1-1/4". Together, they are the perfect high speed Wire-O® finishing solution for today's modern in-plant, digital and « on demand » printing environments, where ease of use, versatility and productivity are a must.

WIRE-O LHERMITE UNIC

A simple plug and play hanger feeder unit can be fitted on the WOB 3500





Lhermite



Versatile

Outstanding productivity

+ Hanger feeder

Easy to use touch screen

FEATURES AND BENEFITS

♦ User-friendly and efficient	Simple touch screen controlling all dynamic size and format adjustments, settings and change overs : no special training required.
	Wire size changeovers in less than 5 minutes. Books delivered onto a static reception tray.

Finishes all 3:1" and 2:1" pitch Wire-O[®] sizes from 1/4" to $1^{-1/4}$ " with maxi 3 skip binds.

Finishes all documents with flush cut and oversize covers as well as tabbed sheets.

Output rates of 500 to 1.000 books per hour depending on format, paper quality and operator skill.

The optional hanger feeder for the WOB 3500 is a simple plug and play unit. It inserts hangers automatically taken from reeled hanger spool or from loose hangers

Output rates of 350 to 500 calendars or books per hour.

Reception of the books



Optional hanger feeder

TECHNICAL CHARACTERISTICS

Binding formats	Minimum : 65 x 80 mm (2- ^{1/2} " x 3- ^{1/4} ") Maximum : 350 x 350 mm (14" x 14")
Wire sizes	Minimum : size n° 4 (1/4 ") Maximum : size n° 20 (1- ^{1/4} ")
Book thickness	1.5 mm to 28 mm (0.6" to 1.1")
Skip bind	In 3:1" : pitch min. 2 x 8 loops, maxi. 2 x 19 loops with a spacing of min. 3 loops and maxi 25 loops En 2:1" : pitch min. 2 x 5 loops, maxi. 2 x 13 loops with a spacing of min. 2 loops and maxi 18 loops
Hanger format	N° 3 - 76 mm mini - 150 mm maxi.
Hanger feeder capacity	100 pcs
Voltage requirements	220-240 V – 1 ph - 50 Hz 110 V – 1 ph – 60 Hz
Dimensions	2110 mm (83") W x 830 mm (33") D x 1180 mm (46.45") H
Nett weight	290 kg (637 lbs)

In line with our policy of continuous development, we reserve the right to change specifications and machine styling, so information presented here may be liable to change.

