



DigiCoater Pro 400
Flat Sheet Coater - HD LED | Cold UV

DigiCoater Pro 400 with VFX or VFL Feeder

Morgana DigiCoater Pro 400

UV coating gives the perfect finish that **enhances, protects** and **adds value** to your printed sheets.

UV Coating is rapidly being adopted as a means to enhance, protect and add value to your digital and litho printed documents. The application of a gloss UV Varnish can be used enhance the print quality, making colours appear richer and more vivid, as well as offering protection for documents being frequently handled.

UV Coating is widely considered as being a more environmentally friendly alternative to lamination as virtually no waste is produced in the production process. Unlike laminated stocks, which normally should be treated as plastic waste, UV coated stocks can be disposed of, or recycled as normal printed paper would be.

Features and Benefits

- Rub resistance – provides a more robust finish when the stock needs to be handled often, or pass through other finishing or mailing systems
- High speed – up to 60m/m on LED systems
- Suitable for inline and offline applications
- Duplex coating option available
- Optional automatic feeding and stacking units available
- Lowest cost per sheet achievable on any machine in its class. Coated sheets are a fraction of the cost of laminated sheets.
- Optional unique IR lamp system necessary for typical wax based toner.
- Low coating coverage needed in order to complete the curing process, only 2 to 4 grams per sq/mtr
- 40% less power needed in order to cure compared to open lamp systems
- Up to 45 metres per minute dependant on stock and type of print
- Extended lifetime on the LED diodes



Unique curing process

Morgana HD LED & Cold UV coaters have removed the risk involved with high temperature conventional UV coaters, eliminating the risk of scorching any substrates. The 'sleep mode' brings the power consumption of the lamps down by 70%. All unpleasant odours on the substrate or the machine are eliminated. The large diameter rollers and optional fluid pre-heating provide a superior finish.

Once coated, the stock is delivered at room temperature - so there is limited distortion or shrinkage of the sheets.

VFX Feeder Key Features

- Up to 5400 sheet capacity
- Two tray configuration allows for uninterrupted job production
- Adaptive Fan Control automatically adjusts air flow for varying media
- Advanced double sheet detection with infrared and ultrasonic sensors
- Max sheet size 356 x 660mm
- Used across all Morgana booklet making platforms




VFL Feeder Key Features

- Up to 2000 sheet capacity
- Adaptive Fan Control automatically adjusts air flow for varying media
- Advanced double sheet detection with infrared and ultrasonic sensors
- Max sheet size 385 x 1300mm
- Up to 600 gsm dependant on machine configuration and stock




DigiCoater Pro 400 - configurations


Configuration Options – Single side



Configuration Options – Double sided



Deep Pile Stacker and Trolley



The deep pile stacker is the production option for customers with longer run lengths, stacking up to 5400 sheets. The trolley design simplifies transporting of the finished stack to the next step in the finishing process

Morgana Mini Stacker

The Morgana Mini Stacker is a simple and cost-effective way of stacking the finished sheets for shorter runs. Once filled, it can be easily wheeled away to move the job to another location for the next step in the finishing process.



Technical Specifications


Morgana DigiCoater Pro 400 CUV

Speed per min (UV)	20-45 meters
Lamp technology	Enclosed Cold UV Quartz with constant PLL controlled cooling
Lifetime Cold UV bulb or lamp	1,500 hours
IR Station	optional
HD function	optional
Applied coating	2-4 grams / square meter
Voltage	3 x 400 V + N + G (EU)
Amperage	20 amp - 400 V (EU) / 32 amp
Air knife	standard
Certifications	CE - ETL - UL/ULC (in progress)
Hot air extraction is needed	


Morgana DigiCoater Pro 400 LED

Speed per min (LED)	20-60 meters
Lamp technology	Air Cooled LED
Lifetime LED	20,000 hours on diodes
IR Station	optional
HD function / Module	optional
Applied coating	2-4 grams / square meter
Voltage	3 x 400 V + N + G (EU)
Amperage	20 amp - 400 V (EU) / 32 amp
Air knife	standard
Certifications	CE - ETL - UL/ULC (in progress)

Single sided coating system with VFL feeder and mini stacker



Double sided coating system with VF feeder and mini stacker



*Disclaimer As part of our continued product improvement plan, specifications and information published here are subject to change without notice. All specifications are dependent on application, type of stock, temperature, RH and print engine used. Specifications quoted were measured on uncoated and unprinted stock. E & OE.