

BX TANK SUPPLY

TANK CONVERSION TO OPEN TOP

OPEN TOP TANK CONVERSION

6"x6"x1/4" Angle Iron for Frame: 4"x4"x1/4" Sq. Tubing for cross members: (4) Lifting Eyes Available (upon request): New valves installed Front(input & Suction) and Rear(drain): New Man-Way gaskets: New DOT Tape: New Mudflaps: New Lights and wiring as necessary: Brakes and tires checked and repaired/replaced as necessary: We can add new custom penetrations (i.e. 4" upfitted to 6" or 8"): existing penetrations can be Blinded upon request

OPTIONS

Interior Blast: White Metal Blast SSPC-SP5 W/2-3 mil Anchor Profile

Interior coating:

- Regular liner Carboline Phenoline Tank Shield 17-20 mil DFT;
- Acid Liner Sherwin Williams Nova Plate 325 18-21 mil DFT, 37%HCL

Interiors are holiday tested using a Tinker-Razor MultiMeter Voltage Holiday-Pinhole Detector

Exterior Blast: Near White Metal Blast SSPC-SP10 W/1-2 mil Anchor Profile

Exterior Coating:

- Carboline Carbothane 8812/8845 DTM High Gloss 3-5 Mils DFT

We offer Custom Interior Coatings - Custom Exterior Coatings

To the best of our knowledge the technical data contained herein are true and correct at the date of issuance and are subject to change without prior notice. No guarantee of accuracy is given or implied because variations can and do exist. NO WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY BX TANK SUPPLY LLC, EITHER EXPRESSED OR IMPLIED.



Email:
sales@bxtanksupply.com

Or call:
(208) 559-6756