

NEW

UltraVu® II 3360

THERE'S A WORLD OF OPPORTUNITY OUT THERE.

VUTEK **it.**

And profit.



- billboards
- point-of-purchase advertising
- banners and signage
- posters
- exhibition graphics
- backlit displays
- display graphics
- fleet graphics
- vehicle graphics
- bus shelters
- bus wraps
- wall murals
- long-term outdoor graphics
- stage graphics
- flags

The UltraVu® II 3360 family of three-meter, superwide digital printers offers you the versatility of both high-speed and high-quality printing.

- Available in four-, six- and eight-color models.
- Eight-color model allows you to easily convert between super-fast-quality printing and photo-quality printing.
- The eight-color model can be configured in two ways:
 - 1) Two channels per color (CMYK) for high-speed, four-color, outdoor applications,
 - 2) One channel per color (CMYK, plus light cyan, light magenta, light yellow and light black) for significantly enhanced, photo-realistic, eight-color images.
- Two-sided printing: Automated alignment system that enables the production of consistent, distortion-free double-sided-graphics.
- Prints on a wide variety of substrates, including vinyl, pressure-sensitive, paper, mesh and textiles.
- Prints up to 10 feet (3 meters) in width.
- 720 dpi resolution (360 dpi addressable) produces images that are sharp, crisp and consistent.
- Prints up to 1622 square feet (151 sqm) per hour.

We provide the industry's best service and support:

- Factory training
- 24/7 technical support
- Applications assistance
- Marketing tools



VUTEK®
A DIVISION OF **efi**

UltraVu® II 3360 Product Specifications

Printing Technology:

- Piezo drop-on-demand inkjet technology
- 720 dpi apparent resolution (360 dpi addressable)
- One-year printer warranty (includes piezo inkjet heads, which are not considered to be consumables with VUTEK printers)
- Extended ink-system warranty available using VUTEk inks
- Heads require minimal maintenance
- 24/7 technical support

Media/Handling:

- Size: rolls with 126" (320 cm) maximum width, 125" (318 cm) maximum print width
- Type: vinyl, pressure-sensitive, paper, mesh and textiles
- Two-sided printing: Automated alignment system to print on back side
- Optional unwind and rewind accessories available

Print Models:

- The UltraVu® II 3360 can be purchased in three variations:
 - Four-color
 - Six-color
 - Eight-color, switchable to Fast-4™ color
- Four-color and six-color models are upgradeable

UltraVu® II 3360 RIP:

- Excellent color reproduction to match original artwork
- Intuitive graphical user interface for easy operation and calibration
- Multi-language graphical user interface
- Gamma control over global brightness

Additional RIP Features:

- ICC color management
- Light CMYK support for smooth highlights to mid-tone transitions, improved color quality, and increased apparent higher resolution
- Tiling feature to simplify complex printing jobs
- Automated contour cutting support

Formats:

- All popular desktop file formats, including PostScript®3™, EPS, TIFF, PDF, RGB/CMYK

Control Station:

- Windows® operating system
- UltraVu 3360 operating software
- DVD Reader
- 1 GB Ethernet adapter

Environmental Considerations:

- Compressed Air: 80 psi (5.63 kg/cm) minimum, 150 psi (10.56 kg/cm) maximum
- 4 cfm (0.056 m³/m) dry air only
- Temperature: 68° F to 85° F (20° C to 29° C)
- Humidity: 20% to 80% (non-condensing)



- Weight: 3851.0 lbs. (1746.8 kg) featuring lightweight Uni-Frame construction
- Height: 62.0" (157.5 cm)
- Width: 236.0" (599.4 cm)
- Depth: 50.0" (127.0 cm)
- Electrical: 3 phase, 40 amps (4 or 5 wire), 200-240 VAC, 50/60 Hz

Inks:

- VUTEk supplies ink in four 3.25-liter bottles in cyan, magenta, yellow, black, light magenta, light cyan, light yellow and light black
- VUTEk inks are solvent-based and carry a two-year warranty (extended to a five-year warranty with Aquashield)
- VUTEk also supports 3M's five-year MCS, Hunt five-year soft-sided fleet, and Hunt/Avery five-year fleet warranties

Productivity:

Print output speed in square feet/square meters per hour

Model

Mode/Speed

UltraVu® II 3360 FC

(4 Channel)
@ 120" width (305 cm)

Enhanced/Max
Ultra/Max

632/59
341/31

UltraVu® II 3360 SC

(6 Channel)
@ 120" width (305 cm)

Enhanced/Max
Ultra/Max

632/59
341/31

UltraVu® II 3360 EC

(8 Channel)
@ 120" width (305 cm)

Enhanced/Max
Ultra/Max

632/59
341/31

UltraVu® II 3360 EC

Fast-4™ (4 Color) x 2
@ 120" width (305 cm)

High/Max
Enhanced/Max
Ultra/Max

1622/151
1150/107
659/61

All trademarks used herein are the property of VUTEk Inc. or other companies. Windows® is a registered trademark of Microsoft Corporation. PostScript® is a registered trademark of Adobe Corporation. Product specifications are subject to change without notice.

© 2004 VUTEk Inc. Printed in U.S.A.



VUTEK
Headquarters & Manufacturing
One VUTEK Place
Meredith, NH 03253 USA
T. 603-279-4635
F. 603-279-6411
e-mail: sales@vutek.com
www.vutek.com

D2003-A 070805 REV G

VUTEk Belgium BVBA
Sales & Support Center
Ikaros Business Park
Ikaroslaan 20, B-1930
Zaventem, Belgium
T. +32-2-749-9420
F. +32-2-749-9465