

USED KUHNE 5-LAYER BLOWN FILM COEX LINE FOR SALE

- Year 2012
- 5 layers
- Film structure: ABCDE
- Materials: LDPE, LLDPE, MDPE, PP, EVA.
- Max Film Width 2.000 mm (79")
- Output 500 kg/h (1100 lb/h)
- Extruder A: 72 mm (2.83"). Gravimetric OCTAGON 5 components.
- Extruder B: 60 mm (2.36"). Gravimetric OCTAGON 4 components.
- Extruder C: 72 mm (2.83"). Gravimetric OCTAGON 5 components.
- Extruder D: 60 mm (2.36"). Gravimetric OCTAGON 4 components.
- Extruder E: 72 mm (2.83"). Gravimetric OCTAGON 5 components.
- Die 350 mm (13.8"). Inserts for 1.5 mm (59 thou) and 2.8 mm (110 thou) die gap.
- IBC
- SMART AIR RING LIP MAXIMIZER.
- Automatic thickness control: K DESIGN.
- Motorized calibration basket (bubble cage) height & diameter. Silicone rollers.
- Automatic width control
- Motorized gusseting boards, width up to 400 mm (15.75"). CFK rollers with felt/wood combination
- Oscillating primary nip. TFE-Lok coated driven roller and silicone coated non-driven roller. Turning bars with microporous surface.
- Secondary nip. TFE-Lok coated driven roller and silicone coated non-driven roller.
- Corona treater: AFS
- Web guide
- Back-to-back winders
- Max Winding Diameter 1,200 mm (47")













Adolfo Edgar
KUHNE Anlagenbau GmbH
March 2021









