

Size	Linear Mass lb/ft		Outside diameter		Wall thickness		Type of end-finish					
	Nonupset T & C	Ex- Upset T & C	In.	mm	In.	mm	Grade					
							J-55	L-80	N-801, Q	C-90	T-95	P-110
2 3/8"	4.00	--	2.375	60.33	0.167	4.24	PN	PN	PN	PN	PN	--
	4.60	4.70	2.375	60.33	0.190	4.83	PNU	PNU	PNU	PNU	PNU	PNU
	5.80	5.95	2.375	60.33	0.254	6.45	--	PNU	PNU	PNU	PNU	PNU
	6.60	--	2.375	60.33	0.295	7.49	--	P	--	P	P	--
	7.35	7.45	2.375	60.33	0.336	8.53	--	PU	--	PU	PU	--
2 7/8"	6.40	6.50	2.875	73.03	0.217	5.51	PUN	PNU	PNU	PNU	PNU	PNU
	7.80	7.90	2.875	73.03	0.276	7.01	--	PNU	PNU	PNU	PNU	PNU
	8.60	8.70	2.875	73.03	0.308	7.82	--	PNU	PNU	PNU	PNU	PNU
	9.35	9.45	2.875	73.03	0.340	8.64	--	PU	--	PU	PU	--
	10.50	--	2.875	73.03	0.392	9.96	--	P	--	P	P	--
	11.50	--	2.875	73.03	0.440	11.18	--	P	--	P	P	--
3 1/2"	7.70	--	3.500	88.90	0.216	5.49	PN	PN	PN	PN	PN	--
	9.20	9.30	3.500	88.90	0.254	6.45	PNU	PNU	PNU	PNU	PNU	PNU
	10.20	--	3.500	88.90	0.289	7.34	PN	PN	PN	PN	PN	--
	12.70	12.95	3.500	88.90	0.375	9.52	--	PNU	PNU	PNU	PNU	PNU
	14.30	--	3.500	88.90	0.430	10.92	--	P	--	P	P	--
	15.50	--	3.500	88.90	0.476	12.09	--	P	--	P	P	--
	17.00	--	3.500	88.90	0.530	13.46	--	P	--	P	P	--
4"	9.50	--	4.000	101.60	0.226	5.74	PN	PN	PN	PN	PN	PU
	--	11.00	4.000	101.60	0.262	6.65	PU	PU	PU	PU	PU	PU
	13.20	--	4.000	101.60	0.33.	8.38	--	P	--	P	P	--
	16.10	--	4.000	101.60	0.415	10.54	--	P	--	P	P	--
	18.90	--	4.000	101.60	0.500	12.70	--	P	--	P	P	--
	22.20	--	4.000	101.60	0.610	15.49	--	P	--	P	P	--
4 1/2"	12.60	12.75	4.500	114.30	0.271	6.88	PNU	PNU	PNU	PNU	PNU	--
	15.20	--	4.500	114.30	0.337	8.56	--	P	--	P	P	--
	17.00	--	4.500	114.30	0.380	9.65	--	P	--	P	P	--
	18.90	--	4.500	114.30	0.43	10.92	--	P	--	P	P	--
	21.50	--	4.500	114.30	0.500	12.70	--	P	--	P	P	--
	23.70	--	4.500	114.30	0.560	14.22	--	P	--	P	P	--
	26.10	--	4.500	114.30	0.630	16.00	--	P	--	P	P	--

Non-Upset T & C—

Ex-Upset T & C—

P—/Plain end

N—/Non-upset threaded and coupled

U—/External upset threaded and coupled