# **PFC SERIES MODELS**

#### **VENTLESS/HOODLESS COUNTERTOP DEEP FRYER**













PERFECT FRY COMPANY LLC Mailing Address: P.O. Box 501 Concord, NH 03302-0501 Shipping Address: 10 Ferry St. Concord, NH 03301

GENERAL INFORMATION: Phone: 1-603-225-6684 Fax: 1-603-225-8472 Email: profits@perfectfry.com

L10-378 R5

www.PerfectFry.com

The Benchmark in Ventless Deep Frying

**SELF VENTING** 

**ODORLESS** 

**HEPA STYLE AIR FILTRATION** 

 INTEGRAL FIRE SUPPRESSION

 PROGRAMMABLE CONTROLS

EASY TO CLEAN

**SMALL FOOTPRINT** 

LARGE OUTPUT


MODULAR DESIGN




# **CLEARANCES**

#### **CLEARANCES**

1" all around and 0" on top.





### **SPECIFICATIONS TABLE**

MODEL		PFC570	PFC375	PFC570	PFC187
ORDER NUMBER		Contact Customer Service, 603-225-6684			
POW	ER SUPPLY (volts)	240	240	208	120
CURR	ENT (amps)	24	16	27	16
CIRCU	JIT CURRENT (amps)	30	20	Min 30**	20
CORD	OPTION	Power Cord, NEMA 6-50 Plug	Power Cord, NEMA 6-20 Plug	Power Cord, NEMA 6-50 Plug	Power Cord, NEMA 5-20Plug
POWI	ER (kilowatts)	5.7	3.8	5.7	1.9
CAPA	CITY (lbs/hr)*	60	45	60	30

#### **BASKETS**

# **OPTIONAL BASKET COVER** (ordered separately part no. 6HT002)

## **GENERAL SPECIFICATIONS**

#### (All Models)

Single (3 wire) International models available upon Cycles 50/60 Hz request. Weight 80 lbs (36 kg) \*Based on up to 1 1/2 minute fast fries. \*\*For use on an individual branch Shipping Weight 95 lbs (43 kg) circuit rated 30A minimum. For supply **Shipping Dimensions** Depth 22" (559 mm) connectors, use minimum no. 10AWG wire (30A rated). This fryer must be Width 22" (559 mm) properly connected to a grounded, dedicated 208 VAC single phase circuit Height 27" (686 mm) according to local installation 7.56 ft3 (.214 m3) Shipping Cube standards and codes. Oil Capacity 2 US Gallons (8 L) 304 Stainless Steel Construction \*\*\*Locking Cabinet Option Also Available

Phase

