PRODUCTS INK PAPER DRIVERS & SUPPORT LEARN & CREATE EPSON STORE ABOUT

Sign In | Track My Order | My Account | Reorder List | Product Registration | Help | Shopping Cart

Professional Imaging SureColor S70670



Overview

Features & Benefits

**Detailed Specs** 

**Options** 

Gallery

**Downloads** 

**Product Literature** 

SureColor S-Series Product Line Brochure Sales Reference Guide

Find a Reseller

Request a Print Sample

**Professional Media** 

**Professional Ink** 

**ICC Profiles** 

**Get Drivers & Support** 

# Specifications

#### **Base Printing Technology**

- Advanced MicroPiezo TFP Print Head<sup>A</sup>
- Dual, 10-channel, drop-on-demand, ink jet heads
- 10-cartridge (C, M, Y, K, Lc, Lm, Lk, O + Optional W and MS)
- Epson UltraChrome GSX ink
- · Professional-level solvent-based ink technology



## Printer Nozzle Configuration

Color and Monochrome 720 nozzles per Color Smallest droplet size is 4.2 picoliters

#### Resolution

1440 x 1440 dpi; 1440 x 720 dpi; 720 x 720 dpi; 720 x 360 dpi

## **Dimensions**

Printer (includes printer, stand, take-in & take-up)

103"(W) x 50"(D) x 52"(H) Printer weight: 525 lbs

**Optional Dryer** 

68"(W) x 9.5"(D) x 11"(H) Dryer weight: 20 lbs



# Print Engine Speeds<sup>B</sup>

720 x 1440 dpi, 44-pass (White and Silver)
720 x 1440 dpi, 20-pass (Silver)
720 x 1440 dpi, 36-pass (White)
1440 x 720 dpi, 8-pass
140 SFPH
720 x 720 dpi, 6-pass
190 SFPH
720 x 720 dpi, 4-pass
280 SFPH
720 x 720 dpi, 2-pass
550 SFPH

#### Acoustic Noise Level

Approximately 59.5 dB(A) according to ISO 7779

# Typical Print Job Speeds<sup>B</sup>

Silver Signage 43 SFPH
White Banner Signage 67 SFPH
Decorative Fine Art Reproduction 140 SFPH
Photo Quality Vehicle Wraps 190 SFPH
Everyday Signage Production 280 SFPH
Typical Outdoor Banners 550 SFPH

## Front-End RIP Workflow by ONYX

GamaPrint Pro PANTONE licensed PostScript Language Level 3 Compatible RIP by ONYX. Includes full workflow software with layout, nesting, tiling, custom spot color management, custom media support and RIP queue functionality. Note: For White and silver printing support, please contact ONYX.

The Epson SureColor S70670 is also supported by most leading third-party RIPs and workflows.

### ONYX GamaPrint Pro RIP Requirements

#### Server Workstation:

Windows 7, Vista® or XP (32-bit or 64-bit) 3.2 GHz Intel® i7 or better 6 GB memory recommended

#### **Client Workstation:**

Macintosh® 10.5+, Windows 7, Vista or XP (32-bit or 64-bit)

#### **Printer Interfaces**

Includes as standard one Hi-Speed USB 2.0 (1.1 compatible) and one Gigabit Ethernet port

## Epson UltraChrome GSX Ink

| Ink Cartridge          | (700 ml) |
|------------------------|----------|
| Black                  | T715100  |
| Cyan                   | T715200  |
| Magenta                | T715300  |
| Yellow                 | T715400  |
| Light Cyan             | T715500  |
| Light Magenta          | T715600  |
| Light Black            | T715700  |
| Orange                 | T715800  |
| Optional Ink Cartridge | (600 ml) |
| White (600 ml)         | T715A00  |



### Limited Warranty and Service

Standard one-year on-site next business day service with toll-free phone support Monday thru Friday.

T715B00

Optional Epson SureColor S70670 Extended service plans available for purchase.

#### Printable Area

Maximum paper width 64-inch
Minimum paper width 12-inch
Minimum paper width (Layering) 20-inch
Left and right margins 0.20" (0.40" total)

Left and right margins 0.20" (0.40" total Maximum printable width 63.60-inches

Maximum printable length limited by software application, OS, media length, and RIP

#### Media Handling

Silver Metallic (350 ml)

Media input Single roll-to-roll, minimum 12" wide up to 64" wide

Cut-sheet size 17" x 22" up to

64" wide

Media core compatibility 2" or 3" cored media

Input roll media diameter Up to 9.8"

Input roll media weight Up to 90 lbs.

Media Weight/Thickness from 45 gsm up to 1.0 mm thick

Roll media take-up reel Fully automatic "wind

in'

or "wind out" with tension bar

Output roll media weight Up to 90 lbs.

#### Heavy Roll Media System (Optional)

Power supplied by the printer

Media core compatibility 2" or 3" cored media

Input roll media diameter Up to 11.8"

Input roll media weight Up to 175 lbs.

Output roll media diameter Up to 11.8"

Output roll media weight Up to 175 lbs.



Optional High-Capacity Roll Support (Heavy-roll support up to 175 lbs)

#### Media Heating System

Off or 86° to 122° F (off or 30° to 50°C) Pre Heater Off or 86° to 122° F (off or 30° to 50°C) Platten Heater Off or 86° to 131° F (off or 30° to 55°C) Post Heater

Independently controlled via control panel or front-end RIP

## Epson Intelligent Ink Cartridge<sup>C</sup>

Cartridge fill volume 700 ml each 8 colors total

> 600 ml white 350 ml Silver Metallic

Ink cartridge shelf life 2 years from printed production (recommended) date or 6 months after open

The printer is designed exclusively for use with EPSON cartridges for greater reliability.

#### Image Permanence Ratings

Outdoor permanence ratings are provided by 3M and Avery.

Please See www.averygraphics.com or www.mmm.com for more details

#### **Environmental Characteristics**

Temperature Operating Storage

59° to 86°F (15° to 30°C) -4° to 104°F (-20° to 40°C)

Relative Humidity

20 to 80% (40 to 60%

Operating

recommended)

Recommended storage Installation requirements 5 to 85% (no condensation) Virtually any location with a

typical air conditioning or

other air ventilation system. No forced ventilation or air purification systems requiredD.

## **Electrical Requirements**

Printer Requires Two 110v Outlets Voltage AC 100-120 V, AC 200-240 V 50-60 Hz Frequency Current

10A at AC 200-240 V Included Dryer Requires One 110v Outlet Voltage

50-60 Hz

1A at AC 110-120 V or 0.5A at AC 200-240 V

Power consumption

Frequency

Current

Operating Standby Heaters ON Sleep Power Off

20A at AC 110-120 V or AC 100-120 V, AC 200-240 V

Approx. 800W or Less Approx. 580W Approx. 12W Less than 0.9W or less



## **Products and Accessory Part Numbers**

SureColor S70670 Production Edition (includes Onyx RIP, Stand &

Take-up Reel)

SCS70670PF

SureColor S70670 High Production Edition SCS70670HD

(includes Onyx RIP, Stand & Take-up Reel, Heavy Roll Media System)

SureColor S70670 Ink Starter Pack (Includes 10-350 ml Cleaning Cartridges and One each of 700 ml CMYKLcLmLkO

Cartridges)

SureColor S70670 Ink Starter Pack with WHITE and SILVER (Includes 10-350 ml Cleaning Cartridges, One each of 700 ml CMYKLcLmLkO Cartridges, One 600 ml White Cartridge, and One 350 ml Silver

Metallic Cartridge)

GSXINK-10

GSXINK-8

Additional One-year SureColor S70670 Extended Service Plan - Silver

EPPS5070SB1

Additional One-year SureColor S70670 Extended Service Plan - Gold

EPPS5070GB1

Additional One-year SureColor S70670

EPPS5070PB1

Extended Service Plan - Platinum

Optional High Speed Print Dryer

C890751

Optional Heavy Roll Media System

C12C890761 T699300

Ink Cleaning Kit (for periodic print head cleaning)

Additional Printer Maintenance Kit (same kit that comes with a new printer) T724100

Additional Cleaning Cartridge (for periodic print head washing) T699000

Additional Waste Ink Bottle (for waste ink disposal)

T724000

C64CORE

Additional 64" Wide Media Take-up Core

## **Sign Up For Exclusive Deals & Offers**

Follow us on Twitter

| Email Address | First Name |
|---------------|------------|
| (Required)    | (Optional) |

OTHER EPSON SITES | CORPORATE INFO | JOBS | CONTACT US | EPSON WORLDWIDE

Privacy Policy | Your California Privacy Rights | Terms of Use | Artist Credits | Copyright © 2000-2013 Epson America, Inc.

A The print head is a maintenance part which the user is responsible to replace when necessary. However, Epson covers head replacement while the printer is under the Epson Preferred Limited Warranty and under any Preferred Plus Plan (limited or unlimited number of head replacements, depending on the Preferred Plus Plan purchased). The life of the print head will vary depending on the user's print volume, print patterns and heater temperature for print settings. Doing proper user maintenance of the print head will help prolong its life.

<sup>&</sup>lt;sup>B</sup> All print speeds shown are based upon print engine speed only, in bi-directional mode. Total throughput times depend upon front-end RIP, file size, printer resolution, ink coverage, networking, etc.

<sup>&</sup>lt;sup>C</sup> The printer is designed to use only EPSON ink cartridges and not other brands of new or refilled cartridges, or other brands of ink or bulk ink systems. Using EPSON cartridges is important for reliable performance and high image quality. Epson offers voluntary recycling of spent ink cartridges.

D Based on testing of one printer at a maximum ink duty in a room of 180 m3 and a ventilation coefficient of 2.2 (without any fan or air conditioning). For more information see the MSDS sheets in the download section.