

LEAN BURN NATURAL GAS GENERATORS

INTERNATIONAL MODEL RANGE



50 Hz RANGE

ISSUE 03 - MARCH 2021

MODEL NAME	FUEL TYPE	CONTINUOUS RATING		STANDBY RATING		ENGINE MODEL	AVAILABLE CONTROLS	ALTERNATIVE FUELS CAPABILITY	GRID CODE COMPLIANCE	EMISSIONS COMPLIANCE
		kVA	kWe	kVA	kWe					
C995N5C	NG	1244	995	—	—	QSK60G	PC3.3 / DEIF	—	•	TA Luft / MCPD
C1160N5C	NG	1450	1160	—	—	QSK60G	PC3.3	—	—	TA Luft
C1200N5C	NG	1500	1200	—	—	QSK60G	PC3.3 / DEIF	—	•	TA Luft / MCPD
C1400N5C	NG	1750	1400	—	—	QSK60G	PC3.3 / DEIF	—	•	TA Luft / MCPD
C1540N5CB	NG	1925	1540	—	—	QSV91G	PC3.3	Low MN	—	TA Luft / MCPD
C1540N5CC	NG	1925	1540	—	—	QSK60G	PC3.3 / DEIF	—	•	TA Luft / MCPD
C1550P5CD	P	1938	1550	—	—	HSK78G	DEIF	—	—	TA Luft/MCPD
C1600N5CD	NG	2000	1600	—	—	HSK78G	DEIF / ComAp	Coal Mine Methane Low MN	•	TA Luft / MCPD
C1750N5CB	NG	2188	1750	—	—	QSV91G	PC3.3	—	—	TA Luft / MCPD
C1800N5CD	NG	2250	1800	—	—	HSK78G	DEIF / ComAp	Coal Mine Methane Low MN	•	TA Luft / MCPD
C2000N5C	NG	2500	2000	—	—	QSV91G	PC3.3	Low BTU	—	TA Luft / MCPD
C2000N5CB	NG	2500	2000	—	—	QSV91G	PC3.3	—	—	TA Luft / MCPD
C2000N5CD	NG	2500	2000	—	—	HSK78G	DEIF / ComAp	Coal Mine Methane Low MN	•	TA Luft / MCPD

- Option
 - Not Available
- NG** Natural Gas
P Propane

For more product information contact your local Cummins distributor or visit cummins.com

Data & Specification sheets available at powersuite.cummins.com

Specifications may change without notice.

60 Hz RANGE OVERLEAF

LEAN BURN NATURAL GAS GENERATORS

INTERNATIONAL MODEL RANGE



60 Hz RANGE

ISSUE 03 - MARCH 2021

MODEL NAME	FUEL TYPE	CONTINUOUS RATING		STANDBY RATING		ENGINE MODEL	AVAILABLE CONTROL	ALTERNATIVE FUELS CAPABILITY	EMISSIONS
		kVA	kWe	kVA	kWe				
C1000N6	NG	—	—	1250	1000	QSK60G	PC3.3 / DEIF	—	EPA NSPS / EPA MOH
C1000N6C	NG	1250	1000	—	—	QSK60G	PC3.3 / DEIF	Low BTU	EPA NSPS Capable
C1100N6C	NG	1375	1100	—	—	QSK60G	PC3.3 / DEIF	Low BTU	EPA NSPS Capable
C1250N6	NG	—	—	1563	1250	QSK60G	PC3.3 / DEIF	—	EPA NSPS / EPA MOH
C1350N6	NG	—	—	1688	1350	QSK60G	PC3.3 / DEIF	—	EPA NSPS / EPA MOH
C1400N6C	NG	1750	1400	—	—	QSK60G	PC3.3 / DEIF	—	EPA NSPS / EPA MOH
C1540N6CB*	NG	1925	1540	—	—	QSV91G	PC3.3	Low MN	EPA NSPS Capable*
C1550P6CD	P	1938	1550	—	—	HSK78G	DEIF	—	EPA NSPS Capable*
C1600N6CD*	NG	2000	1600	—	—	HSK78G	DEIF	Coal Mine Methane Low MN	EPA NSPS Capable / EPA NSPS Capable*
C1750N6B*	NG	—	—	2188	1750	QSV91G	PC3.3	—	EPA NSPS Capable*
C1750N6CB*	NG	2188	1750	—	—	QSV91G	PC3.3	—	EPA NSPS Capable*
C1800N6CD*	NG	2250	1800	—	—	HSK78G	DEIF	Coal Mine Methane Low MN	EPA NSPS Capable / EPA NSPS Capable*
C2000N6B*	NG	—	—	2500	2000	QSV91G	PC3.3	—	EPA NSPS Capable*
C2000N6CB*	NG	2500	2000	—	—	QSV91G	PC3.3	—	EPA NSPS Capable*
C2000N6C*	NG	2500	2000	—	—	QSV91G	PC3.3	Low BTU	EPA NSPS Capable*
C2000N6CD*	NG	2500	2000	—	—	HSK78G	DEIF	Coal Mine Methane Low MN	EPA NSPS Capable / EPA NSPS Capable*

* Has a Gear Box
— Not Available

NG Natural Gas
P Propane

EPA NSPS Certified for stationary emergency applications
EPA MOH Certified for mobile applications

EPA NSPS Capable Certified in the field
EPA NSPS Capable* Certified in the field with an oxidation-catalyst

For more product information contact your local
Cummins distributor or visit cummins.com

Data & Specification sheets available at powersuite.cummins.com

Specifications may change without notice.

50 Hz RANGE OVERLEAF

©2021 Cummins Inc., Box 3005, Columbus, IN 47202-3005 U.S.A. Bulletin 5600281 Produced in U.S.A. Rev. 3/21