

SPECIFICATIONS

Model	AL-MEISTER ALM3230
Paper Feeding Method	Pick Up By Rubber Roller On Upper Side Of Paper
Feeder Pressure Adjustment	Square Holes + Lever
Lamination Method	Heat Roller Method
Film Width	320mm
Film Material	PET
Film Thickness	30mic - 125mic
Film Type	Gloss & Matt
Paper Thickness	0.07 ~ 0.25mm
Paper Size(Width)	257 ~ 330mm
Paper Size(Length)	182 ~ 457mm
Laminating Speed	1.0m/min fixed
Heating Method	Internal Heating Method
Temperature Range	OFF, 80 ~ 130°C
Warm-Up Time	Approx. 15 min.
Cutting	With Margin(3.0mm), Without Margin
Cut Adjust	Front: -30~+ 5mm, Rear: -5~+ 30mm
Fine Adjustment Function Of Slitting Position	Available(Free Fixing Type: Long Hole + Screw) Minimum Finish Size: 248mm
Stand	Not Available
Fine Mode	Not Available
Long Mode	Available (optional)
Power Consumption	1200W
Dimensions	W 1272 × D 630 × H 470mm (Assembled, including roll-up lever
Weight	Aprx. 50kg
RFID	Equipped (One on lower side)

*Corners are square cut.
*Cutter and Trimmer Blades have a approximate life cycle of 50.0000 cuts, A4 size paper
*Warm-up time may differ according to the environment.

AL-MEISTER®
ALM3230
Auto Laminator



Everbest 74
5741 PM Beek en Donk
Tel. +31(0) 492 392 303
www.fujipla.eu

*The next generation of Fujipla Automatic Digital Laminators.
Fully automated operation will reduce both production time and costs.
ALM3230 can laminate simply at the touch of a button.
Easy switching from Encapsulation (with margin) to four edge trimmed
(no margin). Suitable for A4, A3 (trimmed) and SRA3 and banner length
lamination (un-trimmed)*

Automatic Feeder

The advanced automatic feeder will handle up to 200 sheets of paper, based on 80gsm. An anti-skew mechanism is built into the feeder tray allowing correction of sheets before feeding. The positive wide feeding rollers ensure stable sheet feeding for excellent lamination. Quality feeding, less operator involvement, higher efficiency.

Features:

- * Fully automatic machine feeds, laminates, cuts and trims, delivers fully finished.
- * Hot roller system, scratch free lamination and low noise output.
- * Speed 1.0 m/min fixed.
- * Cut adjust for front and back, cutting has adjustment from +0.5mm to -30mm.
- * Skew correction and stable feed combine to eliminate skewed feeding.
- * IC tag reader equipped.

AL-MEISTER® **ALM3230** Auto Laminator



Automatic Trimming

AL-Meister automatically detects the length of the paper and selects the appropriate settings, A4 & A3 size.

There are two types of configuration:

- * Trimming with margin, which guarantees the laminated paper is durable and waterproof.
 - * Trimming without margin, which provides image enhancement and surface protection.
- The modes can be changed easily and the margins are fully adjustable.

Professional Hot Roller System

Hot roller system incorporating high performance heaters. Perfect temperature control for smooth and flawless lamination. Scratch free lamination for perfect results.

A variety of film is available for every job.
Thickness 38-75-125 mic. (gloss & mat)