



WS Series



For OCC and other shredding applications



Key Features:

- Single Tension Cylinder ~ *heavier bales*
- Auto-Tie ~ *Pulls the Wire Across vs. Push*
- On Casters ~ *for ease of cleaning*
- Sub Floor & Liner System ~ *lower maintenance cost*
- Standard Options ~ *greater value!*

Bellevue, Ohio
800-843-7512
www.americanbaler.com

WS Series

Models: 42W; 48W
Bale Size: 43" x 43" x variable;
48" x 42" x variable
Main Cylinder: 8", 9" or 10" bore
trunnion design
System Pressure: 3000 psi
Main Motor: 30, 50, 75 or Twin 30 HP
Feed Type: Conveyor(s), loader Bale
Tying: Five-wire auto-tie (Pull
Through Design)
Shear: Available with or without
adjustable shear blade
Optional: Fluffer
Meets all current ANSI 245.51 Safety
Standards

PRODUCTION OPTIONS

Remote Floor Mounted Power Unit
Additional 4' Bale Tables
Infrared Sensor and Alarm with Wiring
AR300 Charge Box Side Sheets
Side Load Feed Hopper
(Flared One Side or Both Sides)
Fluffer Package
Fluffer Blank (placeholder for future fluffer)
Off-side tier controls
Hi-Lo Multi-Height Floor
Hydraulic oil shipped in baler reservoir
Wire run out sensors
Increase conveyor controls up to 7.5HP
Water Mist (4 Nozzle)
Bulk Wire System
Slip sheet slot



Distributed By: