

# SX PLUS 10/40 LFP



## Key Features

- Single Phase Output
- User-friendly control and operator interface
- GSM Remote monitoring
- Stackable (up to 2 units)
- Easy handling
- Simple and fast commissioning



## Output Specifications

Nominal Output power (continuous)	kVA	10
Peak Output power (5s)	kW	20
Rated voltage (single phase)	V	230
Frequency	Hz	50
Phase (s)		1
Nominal energy capacity	kWh	38.4
Reference ambient temperature	°C	25



## System data

System pass-through capacity	A	80
Operating temperature range	°C	-10.. +50
Degree of protection	IP	44
Noise pressure @1m (LpA)	dB(A)	56.7



## Inverter

Quantity	n.	1
Rated apparent power	kVA	10
Power factor / Range		±0.8



### Battery specifications

Battery modules quantity	n.	8
Battery (Type)		Li-Ion LFP
Module capacity	kWh	4.8
Battery rated Voltage	VDC	48
Depth of Discharge (DoD)	%	90
Battery design life	cycles	6000
Usable energy @ DoD / AC side	kWh	33.2
Total batteries weight	kg	320



### Instruments, controls & connections

Inverter protection Short Circuit	✓
Inverter protection Overload	✓
Inverter protection Over Temperature	✓
Inverter protection Low Battery	✓
System status control panel	✓
Battery condition	✓
Battery main isolator	✓
Remote monitoring device	✓
Automatic generator auto-start signal	✓



### Input Power Connection

16A CEE 2P+T - GRID	1
63A CEE 2P+T - DG	1




### Output Power Connection

16A Schuko	1
16A CEE 2P+T	2
32A CEE 2P+T	1
Individual RCD 1phase sockets	✓




### Overall Dimensions

Length	(L) mm	1077
Width	(W) mm	1105
Height	(H) mm	1130
Weight	kg	670



### Optional

1xSolar Charge Controller 5.8kW 250V	MPPT
Cold Weather Kit	CWK



The information is aligned with the Data file at the time of download.  
Printed on 30/04/2026 (ID 195269)

©2026 | PR Industrial S.r.l. – Loc. Il Piano – 53031 Casole d'Elsa (SI) – ITALY. Company subject to the management and coordination of Generac Power Systems Inc. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice