

SEAL® 54 Base

Laminator



The SEAL 54 Base laminator represents SEAL's latest offering to the rapidly moving digital display market. Ideal for mounting and laminating pressure-sensitive graphics up to 55.1", this machine represents a flexible package at an affordable price - without compromising its functionality.

The SEAL 54 Base is a pressure-sensitive machine with heat assist on the top roller that ensures superb results with a wide range of materials. Whatever the experience level of the operator, the SEAL 54 Base is easy-to-use and will deliver genuine flexibility and high performance levels for the small to medium sized user.

Ideal for sign makers, the 54 Base delivers great capability at an affordable price. It allows users to finish their images and create more applications quickly and easily which results in greater profitability. This laminator is also suitable for small to medium display-based businesses who want to expand their range of applications, but have no need for an encapsulating machine.

The SEAL 54 Base is ideal for producing a wide variety of display graphics (pressure sensitive materials only):

Rigid Indoor Displays Rigid Outdoor Displays Backlit Displays Pop-Up Displays Roll-Up Displays Floor Graphics













The SEAL 54 Base provides the following features:

Optimum performance

- 55.1" working width to handle a wide range of media
- Adjustable pressure and speed settings for maximum versatility
- 2" nip opening to cover a wide range of substrates including road signs with the use of a sled
- Heat assisted top roller for superb lamination performance
- 16.4'/min. max speed for improved productivity
- Manual nip adjustment for precise operation
- Robust, free standing design

Ease of use

- Ergonomic control panel for ease of
- Auto-grip shafts for user friendly webbing
- Swing-up feed table to facilitate easy set up

Safety

- Foot switch for hands free operation
- Self checking safety eyes for increased operator safety
- CE certified

SEAL® 54 Base

Technical Specifications

Maximum Working Width 55.1" (1400 mm) Maximum Speed 16.4ft/min. (5m/min.) Maximum Substrate Thickness 2" (50 mm)
Martine une Cule strate This kings
Maximum Substrate Thickness 2" (50 mm)
Maximum Roller Temperature 104°F (40°C)
Roller Heating Single
Width 75" (1905 mm)
Height 52.2" (1326 mm)
Depth (excl. table) 18.8" (477 mm)
Depth (incl. in-feed table) 21.7" (550 mm)
Working Height 35.4" (900 mm)
Net Weight 512 lbs (232 kg)
Shipping Dimensions Width 78.7" (2000 mm)
Height 63.8" (1620 mm)
Depth 35.4" (900 mm)
Shipping Weight 595 lbs (270 kg)
Electrical Requirements 115 VAC
50/60 Hz, 15A NEMA 5-20 plug
Order Code 64341

Ergonomic control panel for ease of use.



Auto-grip shafts for user friendly webbing.



Neschen Americas 7091 Troy Hill Drive Elkridge, MD 21075 U.S.A.

SEAL* Brand is a registered trademark of Neschen Americas

U.S.A. Tel: 800-257-7325 Local: 410-540-8900 Fax: 800-966-4554



Contact your local distributor:



Neschen Americas Canada

Mississauga, Ontario

Canada L4W 1H9

1601 Matheson Blvd E., Unit 4