

## **ProPAK60 (20HP) Specifications**

*Closed-End Manual-Tie Horizontal Shear Baler*

<b>Overall Length</b>	210" 322" w/SB-1552 Rear-Feed Conveyor
<b>Overall Width</b>	88"
<b>Overall Height</b>	73" 124" w/SB-1552 Rear-Feed Conveyor
<b>Nominal Hopper Size</b>	54" Wide x 40" Long
<b>Product Bale Size</b>	60" Wide x 30" High x Adjustable Length (12-50")
<b>Number of Bale Ties</b>	6
<b>Hydraulic Reservoir</b>	150 gallons
<b>No-Load Cycle Time</b>	28 seconds
<b>Ram Face</b>	109 PSI
<b>Ram Thrust</b>	187,000 lbs.
<b>Hydraulic System Pressure</b>	4,200 PSI
<b>Hydraulic Pump</b>	48gpm Piston Pump
<b>Main Cylinder</b>	Dual 5.5" Bore x 88" Stroke
<b>Main Baler Motor</b>	20HP, 208/230/575 Volt, 3-Phase, 60-Cycle, TEFC
<b>Total Press Weight</b>	22,000 lbs. Approx. (27,600 lbs. w/SB-1552 Conveyor)

### **Baler Features**

- UL listed NEMA 4\* control panel
- Shipped with full oil reservoir - Ready-To-Run
- Integrated PLC / Operator interface
- Heavy-duty cooling with thermostatically controlled fan & circulating pump
- Full Bale Eject
- Adjustable and reversible shear blade for longer life
- Long lasting Nyloil wear blocks on ram (no metal-on-metal contact)
- Feed hopper with hinged access door and safety interrupt switch

\*\*Control panel is NEMA 4 indoor rated. Must be guarded from sunlight in outdoor installations.