

Semi-Automatic Stretch Wrapper

MASTERWRAP HD XL

SEMI AUTOMATIC STRETCH WRAPPER



ROBOPAC
USA

PERFORMANCE FEATURES:

Semi-automatic rotary arm stretch wrapping machines are designed for unstable and heavy products.

 **EASY TO USE INTUITIVE
COLOR INTERFACE**

 **EASY FILM INSERTION
SYSTEM AND 250%
PRE-STRETCH**

 **INDUSTRY 4.0, R-
CONNECT READY**



CONTROL PANEL

New 3.5 inches control panel with color graphic display includes 6 programs that can be set.




PGS CARRIAGE

The PGS film carriage is fixed gear 250% power pre-stretch and the force to load (tension) is controlled by a strain gauge, adjusted on the control panel.



MASTERWRAP HD XL SPEC SHEET



Load Capacity:

Maximum Load

Dimensions:

48" W x 48" L x 94" H

Maximum Load Weight:

Unlimited



Film Delivery System

-Fixed at 250%

-Height Sensing: Automatic photo eye

-Film Threading: Patented S-Pattern

-Standard Film Width – 20"



Performance Criteria

-Production Speed:

Up to 25 LPH

-Wrap Arm Speed:
11 RPM



Utility Requirements

-Voltage: 120V, 18.2 A,
50/80 Hz, 1 PH



Safety Features

-Safety Bumper Warning Light

-Safety Alarm

-CE Compliant, UL, CUL

Operator Interface

-3.5" Color LED and JOG
Dial Programmable

Selector

-6 programmable wrapping
menus

ROBOPACUSA.COM

INFO.US@ROBOPAC.COM

