



Dissolver 400XH


Floor type dissolver for premixing, dispersion and end-mixing in batches up to approximately 400 litres of gross volume.

Advantages

- Good homogenizing and dispersion at a low consumption of power
- Motors: 11kW (15HP) or 15kW (20HP)
- Continuous, infinite speed control by means of frequency converter between 500 — 3000 rpm
- Electrohydraulic plant for lifting and lowering of the mixing unit with built-in safety cut-out switch
- Lifting height 600 mm
- Max container volume: 400 litres gross
- Container fastening device for containers with diameter 400 — 750 mm, mounted on the column with built-in safety cut-out switch
- Very strong and stable construction
- 400XH is equipped with a protective tube for the stirring shaft
- Available in both enclosed fan-cooled IP54 execution and EExe de II B/C T4 flameproof execution
- In standard execution, the Dissolver is fully CE/ATEX marked in conformity with the Machine, Low Voltage and EMC Directives.
- Vacuum equipment (optional)

Additional equipment

- A wide range of stirring units
- Container lid and detachable cover plates in stainless steel
- Vacuum equipment



Handing ApS™
 Nordkranvej 5-9, Vassingerød
 DK - 3540 Lyng
 Tel.: +45 48160166
www.handing.dk

Diaf Dissolver 400 XH – 22 kW

Dette dokument er vejledende.
 Der tages forbehold for fejl.
 This document is only guiding.
 We make reservation for possible errors.
 Copyright © By Handing ApS. All Rights Reserved.

Alle mål i mm.
 All measures in mm.

Lager nr. /LH

R1235