

Nilfisk SC25

Daily use – Quick start with Magic tag



1. Inspect and clean all the optical sensors with a microfiber cloth (3D Lidar on top only if available).



2. Place the key and turn on the machine.



3. Enter the PIN code.



4. Press break release to use the machine manually.



5. Fill the solution tank with fresh water, ensure to view the fill tank display on the screen.



6. Fill the chemical tank with appropriate detergent for scrubber dryers.



7. Verify that the battery is charged.



8. Move the machine to a Magic tag.



9. Scan at 20-30 cm from the tag.



10. Select the plan on the right list and press clean – the machine will automatically come back to the Magic tag when finished.

Daily maintenance – When the cleaning is finished



1. Press break release to use the machine manually.



2. Move the machine to a floor drain.



3. Ensure the machine is turned off during the daily maintenance operations.



4. Empty the debris tray and rinse the tank with water.



5. Empty the recovery tank into the floor drain – pinch the hose and control the floor.



6. Remove the squeegee and vac hose, clean the blades and ensure vacuum hole is clear of blockage on both ends.



7. Clean debris tray, main and side brushes.



8. Plug in the external charger and recharge batteries for 2-3 hours for a full charge.

Nilfisk SC25

Daily use – Quick start with Docking station (no scheduled cleaning) – with water exchange



1. Inspect and clean all the optical sensors with a microfiber cloth (3D Lidar on top only if available).



2. Verify that the machine is fully charged and refilled with fresh water.



3. Enter the PIN code.



4. Press the undock command.



5. Fill the chemical tank with appropriate detergent for scrubber dryers.



6. Select the plan on the right list and press clean – the machine will automatically come back to the Docking station when finished.



7. The Docking station will automatically fill the machine with fresh water and recharge the battery.

Daily use – Schedule a cleaning mission with the Docking station



1. Select "Schedule cleaning" under the options menu.



2. Select "New schedule" on the top right of the screen.



3. Select map, section, return point, start time, frequency and then press "Save".

Daily maintenance – When the cleaning is finished



1. Enter the PIN code.



2. Press the undock command.



3. Press break release to use the machine manually.



4. Ensure the machine is turned off during the daily maintenance operations.



5. Empty the debris cage and rinse the tank with water.



6. Remove the squeegee and vac hose, clean the blades and ensure vacuum hole is clear of blockage on both ends.



7. Clean debris tray, main and side brushes.



8. Re-dock the unit when the daily maintenance is completed.

Nilfisk SC25

Daily use – Quick start with Docking station (no scheduled cleaning) – only charging



1. Inspect and clean all the optical sensors with a microfiber cloth (3D Lidar on top only if available).



2. Verify that the machine is fully charge.



3. Enter the PIN code.



4. Press the undock command.



5. Fill the solution tank with fresh water, ensure to view the fill tank display on the screen.



6. Fill the chemical tank with appropriate detergent for scrubber dryers.



7. Select the plan on the right list and press clean – the machine will automatically come back to the Docking station when finished.



8. The Docking station will automatically recharge the battery.

Daily use – Schedule a cleaning mission with the Docking station



1. Select "Schedule cleaning" under the options menu.



2. Select "New schedule" on the top right of the screen.



3. Select map, section, return point, start time, frequency and then press "Save".

Daily maintenance – When the cleaning is finished



1. Enter the PIN code.



2. Press the undock command.



3. Press break release to use the machine manually.



4. Move the machine to a floor drain.



5. Ensure the machine is turned off during the daily maintenance operations.



6. Empty the debris cage and rinse the tank with water.



7. Empty the recovery tank into the floor drain – pinch the hose and control the floor.



8. Remove the squeegee and vac hose, clean the blades and ensure vacuum hole is clear of blockage on both ends.



9. Clean debris tray, main and side brushes.



10. Re-dock the unit when the daily maintenance is completed.