

IVR-L 65/24-2 SET GO!FURTHER

The IVR-L 65/24-2 Set Go!Further is a limited bundle edition with 33% recycled plastic¹⁾ and exclusive accessories: Liquid Advanced DN 50 floor cleaning set.



Order no.

9.991-107.0

- Limited bundle edition with 33% recycled plastic¹⁾
- 360° working radius and practical accessories holder on the machine for effective working
- Suction hose, handle, 2 suction tubes, standard nozzle and floor nozzle for floor cleaning

Technical data

EAN code		4066529237101
Number of current phases	Ph	1
Voltage	V	220 - 240
Frequency	Hz	50 - 60
Air flow	l/s / m³/h	144 / 520
Vacuum	mbar / kPa	235 / 23.5
Container capacity	l	65
Container material		Steel
Rated input power	kW	2.4
Vacuumping type		Electric
Connection nominal diameter		DN 50
Accessory nominal diameter		DN 50
Main filter dust class		L
Filter area for main filter	m²	0.25
Sound pressure level	dB(A)	68
Cable length	m	10
Weight without accessories	kg	40
Weight (with accessories)	kg	49.8
Weight incl. packaging	kg	50.4
Dimensions (L × W × H)	mm	718 × 526 × 1000

Equipment

- Main filter:** Surface filter
- Accessories included in the scope of delivery:** yes
- Automatic filling level shut-off**
- Container emptying:** Mobile collection container

¹⁾ Device only, all plastic parts without accessories.



Visual filling level indicator

- Transparent hose for checking the amount of fluid absorbed.
- The hose is also used for easy emptying.



High robustness, flexibility and modularity

- The machine and chassis feature reinforced wall thicknesses and are designed for continuous industrial use.
- Rotatable hose connection with up to 360° rotatable pipe bend.



Sustainability features

- Design with 33% recycled plastic¹⁾.
- Higher effectiveness when operating with only one turbine.
- Low operating noise of just 68 dB(A).

SUSTAINABILITY ASPECTS OF IVR-L 65/24-2 SET GO!FURTHER
9.991-107.0

Sustainability aspects of Beyond Cleaning		
Recycled plastics share device	%	28.4

ACCESSORIES FOR IVR-L 65/24-2 SET GO!FURTHER 9.991-107.0



		Order no.	Description	
ACCESSORY SETS				
Accessory kit for liquids/chips				
Floor cleaning kit liquid Advanced DN 50	1	9.990-896.0	Advanced liquid floor cleaning set: EVA hose (9.990-926.0), handle (9.990-928.0), 2 x suction tube (9.990-932.0), floor nozzle (9.990-938.0), standard nozzle (9.980-761.0).	■
FILTERS				
Surface filter				
Surface filter PE L 0.25 m²	2	9.980-225.0	Surface filter for dust class L with 360 mm diameter. Made from polyester, with 0.25 m² filter area.	■
EMPTYING SUPPORTS				
Strainer baskets				
Filter basket, stainless steel, Ø 400 mm, 20 l	3	9.980-852.0	Stainless steel strainer basket with 20 l capacity and 1.5 mm hole diameter for separating liquids and shavings.	■
Other emptying aids				
Overfill protection dia. 435 mm	4	9.982-118.0	Float insert, stainless steel, for overfill prevention with ball float, central suction.	□
OTHER ACCESSORIES				
Baffle plate Ø 410 mm	5	9.984-119.0	Baffle plate made from plastic with 420 mm diameter for containers and tanks.	■
Cable drum 25 m (3 x 1.5 ³)	6	9.982-080.0	AC cable drum with 25 m cable, for fixing in accessories holder 6.415-930.0.	□
NOZZLES				
Standard nozzles				
Mouth piece elastic nozzle DN 50	7	9.980-761.0		□
Standard nozzle silicone FDA blue DN-F50	8	9.989-841.0		□
Standard nozzle silicone FDA green DN-F50	9	9.989-842.0		□
Standard nozzle silicone FDA red DN-F50	10	9.989-843.0		□
Standard nozzle silicone FDA transparent DN-F50	11	9.989-844.0		□
Standard nozzle silicone FDA white DN-F50	12	9.989-845.0		□
Standard nozzle silicone FDA yellow DN-F50	13	9.989-846.0		□
Standard PVC nozzle DN50	14	9.989-673.0	Electroconductive standard PVC nozzle. DN 50.	□

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR IVR-L 65/24-2 SET GO!FURTHER 9.991-107.0



		Order no.	Description	
NOZZLES				
Standard nozzles				
Standard nozzle silicone DN50	15	9.988-402.0		☐
Standard nozzle cuttable rubber DN50	16	9.989-675.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 50.	☐
Flexible standard nozzles				
Standard nozzle flexible PVC DN50	17	9.981-421.0	Electroconductive, flexible round nozzle made from galvanised steel, DN 50, with rubber mouthpiece DN 30.	☐
Standard nozzle, flexible, angled 90° PP DN50	18	9.981-430.0	Flexible, electroconductive angled nozzle, DN 50, length: 800 mm.	☐
Floor nozzles				
Floor nozzle stainless steel AISI 316L DN-F50 blue	19	9.989-862.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 green	20	9.989-864.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 red	21	9.989-866.0		☐
Aluminium floor nozzle 200 mm DN50	22	9.981-426.0	Floor nozzle, DN 50, with 200 mm suction width.	☐
Aluminium floor nozzle 370 mm DN50	23	9.989-664.0	Floor nozzle. 370 mm, made from aluminium. DN 50.	☐
Aluminium floor nozzle 500 mm DN50	24	9.989-684.0	Floor nozzle, 500 mm, made from aluminium. Electroconductive. DN 50.	☐
Crevice nozzles				
Crevice nozzle PP 15 mm × 145 mm DN50	25	9.988-117.0	Electroconductive, flat multi-purpose crevice nozzle made from plastic, DN 52.	☐
Crevice nozzle 18 mm × 120 mm DN50	26	9.981-442.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 17 mm slot width.	☐
Crevice nozzle 25 mm × 120 mm DN50	27	9.981-465.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 25 mm slot width.	☐
Flexible crevice nozzles				
Flexible crevice nozzle silicone 65 mm DN50	28	9.988-403.0	Flexible crevice nozzle made from silicone, DN 50.	☐

☐ Available accessories.

ACCESSORIES FOR IVR-L 65/24-2 SET GO!FURTHER 9.991-107.0



		Order no.	Description	
NOZZLES				
Flexible crevice nozzles				
Flexible crevice nozzle 12 mm × 45 mm DN50	29	9.981-424.0	Flexible, electroconductive galvanised crevice nozzle, DN 50, with 13 mm slot width.	☐
Flexible crevice nozzle 20 mm × 45 mm DN50	30	9.981-425.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 50.	☐
Surface nozzles				
Silicone surface nozzle FDA blue DN-F50	31	9.989-850.0		☐
Silicone surface nozzle FDA green DN-F50	32	9.989-852.0		☐
Silicone surface nozzle FDA red DN-F50	33	9.989-854.0		☐
Silicone surface nozzle FDA transparent DN-F50	34	9.989-856.0		☐
Silicone surface nozzle FDA white DN-F50	35	9.989-858.0		☐
Silicone surface nozzle FDA yellow DN-F50	36	9.989-860.0		☐
Silicone surface nozzle 120 mm DN50	37	9.988-119.0	Electroconductive rubber nozzle, angled, DN 50, suitable for use with foods.	☐
Aluminium surface nozzle 150 mm DN50	38	9.989-665.0	Surface nozzle, 150 mm, made from aluminium. DN 50.	☐
Liquid nozzles				
Liquid nozzle 900 mm DN50	39	9.981-427.0	Bypass nozzle, DN 50, overall length: 1000 mm.	☐
Borehole nozzles				
Blind hole nozzle DN40	40	9.989-671.0	90° curved blind hole nozzle with 60 mm diameter.	☐
Blind hose nozzle angled 60° DN40	41	9.989-669.0	90° curved blind hole nozzle with 48 mm diameter. DN 40.	☐
Blind hole nozzle angled 90° DN40	42	9.989-667.0	90° curved blind hole nozzle with 60 mm diameter. DN 40.	☐

☐ Available accessories.

ACCESSORIES FOR IVR-L 65/24-2 SET GO!FURTHER 9.991-107.0



		Order no.	Description	
NOZZLES				
Borehole nozzles				
Blind hose nozzle angled 90° 200 mm extension DN40	43	9.989-670.0	90° curved blind hole nozzle with 48 mm diameter. DN 40.	☐
BRUSHES				
Standard brushes				
Standard brush 40 mm DN50	44	9.981-432.0	Flat brush nozzle DN 50.	☐
End brushes				
Brush FDA blue ø 75 mm DN-F50	45	9.989-874.0		☐
Brush FDA green ø 75 mm DN-F50	46	9.989-876.0		☐
Brush FDA red ø 75 mm DN-F50	47	9.989-878.0		☐
Brush FDA white ø 75 mm DN-F50	48	9.989-880.0		☐
Brush FDA yellow ø 75 mm DN-F50	49	9.989-882.0		☐
End brush Ø 82 mm DN50	50	9.989-608.0	Electroconductive end brush with 82 mm diameter. DN 50.	☐
HOSES				
Hose installation sets				
Hose installation kit DN50	51	9.989-628.0	Multipiece hose connection kit, DN 50.	☐
Hose connection kit, stainless steel AISI 304 DN50	52	9.989-987.0	Hose connection kit in nominal width DN 50, made of stainless steel. Contents: 1 hose connection piece, 1 hose connection (rotating), 2 hose clamps, 2 hose end pieces (black), 1 flat bag (PE plastic).	☐
Hose connection kit, DN50 AISI 304 FDA	53	9.990-346.0	FDA-compliant hose connection kit in nominal width DN 50, made of stainless steel. Contents: 1 hose connection piece, 1 hose connection, 2 hose clamps, 2 hose end pieces (white), 1 flat bag (PE plastic).	☐
PU hoses				
Hose PU, hose connectors stainless steel, DN 50 3 m	54	9.989-968.0		☐
Hose PU, hose connectors stainless steel, DN 50 5 m	55	9.989-969.0		☐
Hose PU FDA, hose connectors stainless steel, DN 50 3 m	56	9.989-973.0		☐

☐ Available accessories.

ACCESSORIES FOR IVR-L 65/24-2 SET GO!FURTHER 9.991-107.0



		Order no.	Description	
HOSES				
PU hoses				
Hose PU FDA, hose connectors stainless steel, DN 50 5 m	57	9.989-974.0		☐
Hose PU FDA DN50 15 m, without connectors	58	9.989-975.0		☐
Hose PU DN50 3 m	59	9.989-619.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	☐
Hose PU DN50 5 m	60	9.989-620.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	☐
PU hose DN50 15 m without connectors	61	9.989-638.0	PU hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 80 °C. Length: 15 m.	☐
ME-PU-hoses				
Hose ME-PU DN50 3 m	62	9.989-623.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 3 m.	☐
Hose ME-PU DN50 5 m	63	9.989-625.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 5 m.	☐
ME-PU hose DN50 15 m without connectors	64	9.989-641.0	Electroconductive, oil-resistant ME-PU hose without tap adapter, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 15 m.	☐
ADAPTERS / REDUCERS / DISTRIBUTORS				
Reducers/expanders				
Reducer DN 70 to DN 50	65	9.977-772.0		☐
Reduction DN50 to DN40	66	9.981-231.0	Reducer from DN 50 to DN 40. Material: Steel. Electroconductive.	☐
Expander				
Expansion DN50 to DN70	67	9.981-921.0	Reducer from external cone DN 50 to internal cone DN 70. Material: Steel. Electroconductive.	☐
Distributor				
Y-piece fitting DN50 to DN40	68	9.981-149.0	Manifold, electroconductive, steel, DN 50/40/40.	☐
PRE-SEPARATORS				
Pre-separator				
Pre-separator station SB 100L	69	9.982-243.0		☐
Pre-separator Tc Op liquids 125 l DN70	70	9.989-686.0	125 litre pre-separator, DN 70.	☐

☐ Available accessories.

ACCESSORIES FOR IVR-L 65/24-2 SET GO!FURTHER 9.991-107.0



		Order no.	Description	
PRE-SEPARATORS				
Pre-separator				
Pre-separator Ef solid materials 100 l DN70	71	9.982-238.0	Mobile pre-separator station with 100 l capacity and discharge flap.	☐
Pre-separator drum 200 l	72	9.989-685.0	Standard drum which complies with the ISO 15750-2 standard.	☐
Pre-separator lid				
Pre-separator lid DN 50, for 200 l drum	73	9.981-659.0		☐
Pre-separator cover Op liquids ø 517 mm DN70	74	9.981-666.0	Pre-separator cover DN 70. Suitable for containers with 517 mm diameter.	☐
Pre-separator cover Op liquids ø 575 mm DN70	75	9.981-662.0	Pre-separator cover DN 70 for 200 litre standard drum (9.989-685.0).	☐
Pre-separator cover solid materials ø 517 mm DN70	76	9.981-665.0	Pre-separator cover DN 70. Suitable for containers with 517 mm diameter.	☐
Pre-separator cover solid materials ø 575 mm DN70	77	9.981-661.0	Pre-separator cover DN 70 for 200 litre standard drum (9.989-685.0).	☐

☐ Available accessories.