HG 64

With our HG 64 hot water generator (64 kW heat output), you can cost-effectively transform any cold water high-pressure cleaner into a hot water machine with higher cleaning performance.

WORLD'S NO. 1 PRESSURE WASHER BRAND

4–6 h

BIODIESEL

Order no.	1.030-510.0

Technical data		
EAN code		4054278262628
Heating output	kW	64
Temperature (for supply 12 °C)	°C	max. 80
55 °C Δ T @	l/h	900
Weight without accessories	kg	124.2
Weight incl. packaging	kg	136.6
Dimensions (L × W × H)	mm	1000 × 850 × 1080

Durable and robust

- Highly efficient, tried-and-tested "Made in Germany" burner technology.
- Tried-and-tested Kärcher safety technology guarantees optimal protection of the machine and user.
- The sturdy pipe frame provides protection in continuous heavy-duty use.

Increased cleaning performance thanks to hot water

- Shorter cleaning times and reduction of labour costs.
- More effective removal of oils, greases and lubricants.
- Germ-killing effect and protection of sensitive surfaces.

Especially easy to maintain

- Easy access to all service and maintenance components.
- Integrated fuel filter and removable fuel tank for cleaning.

HG 64, 1.030-510.0, 2026-09-18

ACCESSORIES FOR HG 64
1.030-510.0

1

2

3

4

6

7

8

9

10

11

12

13

14

		Order no.	Description	
TRIGGER GUNS				
Spray guns				
M22 Classic spray gun	1	4.760-843.0	Classic spray gun with valve. Also suitable for Kärcher hot water high-pressure cleaners.	■
Pistol TR 155°C with package	2	4.119-002.0		☐
EASY!Force Advanced	3	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	☐
EASY!Force conversion kit 2 – from machine	4	4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	☐
SPRAY LANCES				
Spray lance				
Spray lance 850 mm	5	9.751-044.0	The 600-mm long galvanised spray lance with hand screw connection is suitable for machines in the HD Classic range. The spray lance is not rotatable.	■
Spray lance Classic 1,050 mm	6	4.760-855.0	High-pressure spray lance with M 22 screw connections from the Classic series from Kärcher. Also suitable for hot water high-pressure cleaners.	☐
Jet pipe 600mm with package	7	4.760-856.0		☐
Jet pipe Classic M 200mm	8	4.760-887.0		☐
Jet pipe Classic M 400mm	9	4.760-888.0		☐
Jet pipe Classic M 840mm	10	4.760-895.0		☐
250 mm lance, non-rotatable	11	4.760-667.0	250 mm stainless steel lance. With manual coupling. Non-rotatable.	☐
550 mm lance, non-rotatable	12	4.760-665.0	550 mm stainless steel lance. With manual coupling. Non-rotatable.	☐
Rotating spray lances				
Spray lance, 600 mm, rotatable	13	4.760-664.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Spray lance, 840 mm, rotatable	14	4.760-663.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐

■ Included in the scope of supply. ☐ Available accessories.

ACCESSORIES FOR HG 64
1.030-510.0

15


18

19

20–21

22

23

24

25

26

		Order no.	Description	
SPRAY LANCES				
Rotating spray lances				
Spray lance, 1050 mm, rotatable	15	4.760-660.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Spray lance, 1550 mm, rotatable	16	4.760-661.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Spray lance, 2050 mm, rotatable	17	4.760-662.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Angular spray lance				
Spray lance for toilets and rain gutters	18	4.760-073.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	☐
Flexible spray lance				
High pressure articulated joint	19	4.481-039.0	High-pressure articulated joint: Thanks to infinite angle adjustment up to 120°, this tool is ideal to effortlessly clean hard-to-reach areas. Simply attach to the spray lance of the pressure washer.	☐
Jet pipe flexible 0,85m, 850 mm	20	6.394-655.0	1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	☐
Flexible lance, 1050 mm	21	6.394-654.0		☐
Undercarriage spray lance				
Underbody lance	22	4.760-245.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	☐
WEED CONTROL				
WR 50	23	2.643-758.0	In combination with a hot water high-pressure cleaner from Kärcher, the 50 cm wide weed remover WR 50 is ideal for removing weeds. It comes with an adaptive chassis and nozzle adapter.	☐
WR 20	24	2.643-760.0	For thorough weed removal: The WR 20 weed remover for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 20 cm wide nozzle bar and nozzle adapter.	☐
QUICK CONNECT				
Quick coupling	25	6.401-458.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	☐
Male coupling	26	6.401-459.0	Hardened stainless steel male coupling for quick coupling 6.401-458. With M 22 × 1.5 external thread.	☐
DRUM AND TANK CLEANING				
Add-on kit mud sucker	27	2.641-798.0	For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps.	☐
SEALS FOR TRAPEZOIDAL THREAD				
Gasket set with 9x O-rings for TR thread	28	2.880-001.0		☐

☐ Available accessories.

ACCESSORIES FOR HG 64
1.030-510.0

29

30, 37, 39–40

31–32

33

34

35

36

38

41

42

		Order no.	Description	
STEAM JET NOZZLE / NOZZLE PROTECTOR / ROLLOVER NOZZLE				
Rollover nozzle holder				
Owner of jets double brass	29	4.764-012.0	Rollover nozzle holder for contactless changeover from pencil jet to fan jet as well as low-pressure detergent injection via knurled nut. Without nozzle insert. (Additional type-specific power nozzle).	☐
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 30 m, ID 8, 315 bar, 2 × M22 × 1.5	30	6.390-293.0	To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 × 1.5.	☐
High-pressure hose, 15 m, ID 10, 220 bar, 2 × M22 × 1.5	31	6.390-023.0	Connectors at both ends, M 22 × 1.5, with kink protection.	☐
High-pressure hose, 20 m, ID 10, 220 bar, 2 × M22 × 1.5	32	6.390-726.0	with union on both sides, M 22 × 1.5 with anti-kink protection. NW 10/155°C/220 bar	☐
High-pressure hose, 25 m, ID 10, 220 bar, 2 × M22 × 1.5	33	6.391-513.0		☐
High-pressure hose, 15 m, ID 12, 210 bar, 2 × M22 × 1.5	34	6.391-849.0	High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22 × 1.5 with anti-kink protection.	☐
High-pressure hose, 40 m, ID 12, 210 bar, 2 × M22 × 1.5	35	6.391-865.0		☐
Longlife 400				
High-pressure hose Longlife, 20 m, ID 8, 400 bar, 1 × M22 × 1.5 / 1 × AVS-hose reel connection	36	6.390-208.0	20 m high-pressure hose Longlife 400 (DN 8) with patented (rotating) AVS trigger gun connector and manual coupling. Two layer high-strength steel wire reinforced.	☐
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 10 m, ID 8, 400 bar, 2 × M22 × 1.5	37	6.388-083.0	10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 × 1.5, with kink protection.	☐
High-pressure hose Longlife, 15 m, ID 8, 400 bar, 2 × M22 × 1.5	38	6.389-709.0	With rotary coupling, 2 × M 22 × 1.5	☐
High-pressure hose Longlife, 20 m, ID 8, 400 bar, 2 × M22 × 1.5	39	6.390-027.0	with rotary coupling, 2 × M 22 × 1.5	☐
High-pressure hose Longlife, 30 m, ID 8, 400 bar, 2 × M22 × 1.5	40	6.390-294.0	With rotary coupling, 2 × M 22 × 1.5	☐
Longlife food design with screw connections at both ends				
High-pressure hose food grade, 10 m, ID 8, 400 bar, 2 × M22 × 1.5	41	6.391-864.0	Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 × M 22 × 1,5	☐
Special hoses				
High-pressure hose curved, 1.5 m, ID 8, 400 bar, 2 × M22 × 1.5	42	6.388-886.0	Connection hose in longlife quality with 2x M22 × 1.5, with angled connection on one side.	☐

☐ Available accessories.

ACCESSORIES FOR HG 64
1.030-510.0

43

44

45

46

47

48

49

50

51

52

53

54

55–56

		Order no.	Description	
HIGH-PRESSURE HOSES				
Classic				
Hose assembly with package M22 DN10 25MP, 20 m, ID 10, 250 bar × , M22 × 1.5	43	4.760-892.0	High-pressure hose with M22 screw connections from the Classic series from Kärcher. Also suitable for hot water high-pressure cleaners.	☐
FLOOR AND HARD SURFACE CLEANER				
FR 30 Me surface cleaner				
Hard surface cleaner FR 30 Me	44	2.640-355.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	☐
FRV 30 Me surface cleaner				
FRV 30 Me	45	2.642-911.0	The stainless steel FRV 30 Me Surface Cleaner is designed for hot water cleaning up to 85 °C in inside and outside areas. Integrated automatic suction removes dirty water directly during operation.	☐
Extension hose FRV 30 Me and FRV 50 Me	46	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	☐
FOAM SYSTEMS				
Inno Foam Kit				
Inno Foam Set with detergent injector	47	2.640-151.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	☐
Inno Foam Set	48	2.640-692.0		☐
Easy Foam Set				
Easy Foam Set with RM injector	49	2.640-691.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	☐
Easy Foam Set	50	2.640-693.0		☐
Cup foam lance				
1-litre cleaning agent container for cup foam lance basic	51	5.071-414.0	For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0).	☐
1-litre cleaning agent container for cup foam lance advanced	52	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	☐
COUPLING PARTS				
Rotary coupling				
Rotary coupling	53	4.401-091.0	Reliably prevents twisting of HP hoses. Connection M 22 × 1.5 m. Handle protection	☐
Coupling				
Coupler -2 × M22 × 1,5	54	4.403-002.0	For connecting and extending high-pressure hoses. Connection 2 × M 22 × 1.5.	☐
Connector				
Y distributor	55	4.405-048.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	☐
	56	4.111-024.0		☐

☐ Available accessories.

ACCESSORIES FOR HG 64
1.030-510.0

57

58

59

60

61

62

63

64

65

66

67

68–69

70

		Order no.	Description	
COUPLING PARTS				
Adapters				
Sealing cone complete	57	4.424-004.0	In order to install high-pressure hose with male coupling on thread with M22 × 1.5 Alternative:4.111-032.0 Adapter 4 – Device new / Hose old Swivel	☐
EASY!Lock adapter				
Adapter 1 M22AG-TR22AG	58	4.111-029.0	Adapter 1 to connect the old hose with the new hose	☐
Adapter 2 M22IG-TR22AG	59	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	☐
Adapter 3 M22IG-TR22AG	60	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	☐
Adapter 5 TR22IG-M22AG	61	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	☐
Adapter 6 TR22IG-M22AG	62	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	☐
Adapter 7 M18IG-TR20AG	63	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	☐
Adapter 8 TR20IG-M18AG	64	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	☐
Adapter 12 rotary coupling EASY!Lock 22 IG – M22 × 1.8 AG	65	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	☐
HOSE REELS				
Automatic, self-winding hose reels for wall mounting				
Automatic stainless steel hose reel, 20 m	66	6.391-520.0		☐
Automatic stainless steel hose reel, 40 m	67	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	☐
Zinc-coated swivel holder	68	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	☐
Stainless steel swivel holder	69	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	☐
Automatic plastic hose reel incl. high-pressure hose, 15 m	70	2.639-257.0	Spring-mounted and ready-to-use automatic hose reel for wall mounting. Simplifies handling of the high-pressure hose, shortens set-up times and increases occupational safety.	☐

☐ Available accessories.

ACCESSORIES FOR HG 64
1.030-510.0

71

72

73

74

76–77

78

79

80

82

83

84

		Order no.	Description	
HOSE REELS				
Automatic, self-winding hose reels for wall mounting				
Automatic hose reel, powder-coated steel / plastic, 20 m	71	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	☐
Automatic stainless steel / synthetic material hose drum, 20 m	72	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	☐
Automatic hose reel, coated, 20 m	73	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	☐
Hose reel, automatic, basalt grey-coated, 20 m	74	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife).	☐
Automatic hose reel, stainless steel, includes swivel holder, 20 m	75	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	☐
WATER CONNECTION				
Geka coupling				
Geka connector with hose barb, R 3/4"	76	6.388-455.0	with hose liner	☐
Geka connector with hose barb, R 1"	77	6.388-465.0	with hose barb	☐
Geka connector with internal thread, R 1"	78	6.388-458.0	with female thread	☐
Suction filter				
Water suction filter	79	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve	☐
Suction filter with check valve	80	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	☐
Water fine filter				
Universal water fine filter, 25 µm	81	2.637-020.0	Fine water filter, mesh size 25 µm, max. temperature 50° C. Protects the device from dirt particles in the water. Maximum flow rate: 1,200 l/h. Connection 3/4", including 1" adapter.	☐
Water fine filter, with adapter	82	4.730-102.0	Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	☐
Water fine filter, 100 µm, R 1"	83	2.638-270.0	Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	☐
WASHING BRUSHES				
Push-on washing brush				
Push-on wash brush	84	4.762-016.0	For general-purpose cleaning of all surfaces. Clamps directly onto the spray lance. Connection M 18 × 1.5	☐

☐ Available accessories.

ACCESSORIES FOR HG 64
1.030-510.0

85–86

87–88

		Order no.	Description	
WASHING BRUSHES				
Rotating washing brush				
Rotating wash brush for < 800 l/h machines, nylon bristles	85	4.762-561.0	The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60°C. (M 18 × 1.5, replaceable brush insert).	☐
Rotating wash brush for > 800 l/h machines	86	4.762-559.0	Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 × 1.5 (replaceable brush insert).	☐
Rotating wash brush for < 800 l/h machines, natural bristles	87	4.762-560.0		☐
Rotating wash brush for > 800 l/h machines	88	4.762-562.0		☐

☐ Available accessories.