



T600e – T600 - DAILY OPERATOR CHECKLIST

PRE-OPERATION CHECKLIST

- ☐ Sweep area and remove any obstructions.
- ☐ Check the battery fluid. Fill as necessary.
- ☐ Machines with Smart-Fill Automatic Battery Watering option: Check the automatic battery watering tank. Fill with distilled water as necessary.
- ☐ Check the battery charge level. Charge as necessary.
- ☐ Check brushes/pads for wear and damage.
- ☐ Check scrub head skirt for wear and damage.
- ☐ Check squeegee blades for wear, damage and for proper deflection adjustment.
- ☐ Clean the squeegee drip trap reservoir.
- ☐ Check the squeegee vacuum hose for debris or blockage.
- ☐ Confirm recovery tank is empty and clean.
- ☐ Confirm recovery tank debris tray is clean.
- ☐ Confirm recovery tank float shut-off screen is clean
- ☐ Cylindrical brush model - confirm debris trough is empty and clean.
- ☐ ec-H2O Scrubbing: Confirm solution tank is filled with clear cool water only.
- ☐ ec-H2O Scrubbing: Confirm all conventional cleaning agents/restorers are drained and rinsed from solution tank.
- ☐ Check machine for proper operation.

POST-OPERATIONAL CHECKLIST

- ☐ Drain and clean the recovery tank.
- ☐ Remove, clean and reinstall the float shut-off screen.
- ☐ Remove, clean and reinstall the debris tray.
- ☐ Rinse out the recovery tank with clean water.
- ☐ Before using the ec-H2O system, confirm the solution tank is cleaned and filled with clean water.
- ☐ After every 50 hours of operation, drain the solution tank, then remove, clean and reinstall the solution tank filter.
- ☐ Check the battery charge levels to determine if the battery needs charging.
- ☐ Check the fluid level of all battery cells and place the machine on the charger if needed.

List below any problems that occurred during operation.

OPERATOR _____

DATE _____

SUPERVISOR _____

DATE _____